



Terminals & Splices > Terminal Housings, Insulation Sleeves & Blocks > Crimp Terminal Housings



Terminal Type: **Receptacle**
Connector & Housing Type: **Receptacle**
Number of Positions: **1**
Terminal Orientation: **Straight**
UL Flammability Rating: **UL 94V-2**

Features

Product Type Features

Connector & Contact Terminates To	Wire & Cable
Sealable	No
Connector & Housing Type	Receptacle

Configuration Features

Number of Positions	1
---------------------	---

Body Features

Primary Product Color	Natural
-----------------------	---------

Contact Features

Terminal Type	Receptacle
Terminal Orientation	Straight
Contact Mating Retention	With

Mechanical Attachment

Mating Retention Type	Latch
Mating Alignment	With



Connector Mounting Type	Cable Mount (Free-Hanging)
-------------------------	----------------------------

Housing Features

Housing Material	Nylon
------------------	-------

Dimensions

Product Length	25 mm[.984 in]
----------------	----------------

Usage Conditions

Operating Temperature Range	-30 – 105 °C[-22 – 221 °F]
-----------------------------	----------------------------

Industry Standards

UL Flammability Rating	UL 94V-2
------------------------	----------

Packaging Features

Packaging Quantity	100
--------------------	-----

Product Compliance

For compliance documentation, visit the product page on [TE.com](#)>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>



Compatible Parts

TE Part # 176986-2 FF 250 PLUG HSG 1P NYLON BLACK	TE Part # 176986-1 FF 250 PLUG HSG 1P NYLON NAT	TE Part # 880192-1 5W FASTIN-ON REC. H	TE Part # 176987-6 FF 250 PLUG HSG 1P NYLON GRAY
TE Part # 521743-1 FF 250 HOUSING RECEPTACLE NYLON 6/6	TE Part # 176987-1 FF 250 PLUG HSG 1P NYLON NAT	TE Part # 880192-2 5 WAY FF 110 HSG REC NYLON 66 NATURAL	TE Part # 176987-5 FF 250 PLUG HSG 1P NYLON BLUE
TE Part # 170258-2 FF 250 REC 14-12AWG TPBR REREELING	TE Part # 1-626040-0 RELY BASE MOLDING 5W POLYPROPYLENE	TE Part # 176987-4 FF 250 PLUG HSG 1P NYLON GREEN	TE Part # 170258-1 FF 250 REC 14-12AWG BR REREELING

Also in the Series | FASTIN-FASTON 250

Crimp Terminal Housings(192)	Insertion & Extraction Tools(2)	Quick Disconnects(216)


Customers Also Bought




TE Part #HDP26-24-91SE-L015
PLG, 9P, BLK, E, THD, 8/12/16, S



TE Part #170342-2
250 FASTON,REC.,20-14 AWG,TPBR



TE Part #172129-1
250 FASTON HSG, CAP 2P NATURAL




TE Part #172130-1
FF 250 REC HSG 2P NYLON NAT




TE Part #179595-1
AMP POWER D/LOCK TAB CONT. L/P



TE Part #747275-1
037 LP HDF STRAIN RELIEF



TE Part #925324-1
FF 250 REC HSG 1P NYLON BLACK



TE Part #1813139-1
SEALED MT2 6POSN PLUG HOUSING ASSEMBLY



TE Part #5-1825136-4
A101TCQ04



TE Part #2329328-8
PB OFF/ON HC YLW M2 TERM. IP68

Documents

Product Drawings

FF 250 REC HSG 1P NYLON NAT

English

CAD Files

Customer View Model

ENG_CVM_CVM_172128-1_F.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_172128-1_F.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_172128-1_F.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages



White Paper: Nylon Discoloration

English

Product Specifications

Application Specification

English

Instruction Sheets

"250" Series, Housing Lance Connector

Japanese

"250" Series, Housing Lance Connector

Japanese