3SBC1517A2 ✔ ACTIVE


CII | CII 3SBC Relay

TE Internal #: 2-1617072-6

General Purpose Signal Relay, DC, Non-Polarized, Monostable, 2 Form C DPDT-CO, 2 A Contact Rating, 12 VDC Coil Voltage, CII 3SBC Relay

View on TE.com >

Relays & Contactors > Electromechanical Relays > DPDT Relay : Electrically-Held, 1/5-Size Relay



Relay & Contactor Type: **General Purpose Signal Relay**

Coil Magnetic System: **Non-Polarized, Monostable**

Contact Arrangement: **2 Form C DPDT-CO**

Current Type: **DC**

Contact Current Rating: **2 A**

All DPDT Relay : Electrically-Held, 1/5-Size Relay (84)

Features

Product Type Features

Relay & Contactor Type	General Purpose Signal Relay

Configuration Features

Contact Arrangement	2 Form C DPDT-CO

Electrical Characteristics

Coil Resistance	210 Ω
Contact Current Rating	2 A
Coil Voltage Rating	12 VDC
Coil Power Rating DC	.686 W

Body Features

Enclosure Type	Hermetically Sealed

Termination Features

Main Termination & Connection Type	Solder Pins
Coil Termination & Connection Type	Solder Pins

Mechanical Attachment

Product Mount Type	Board Mount

Usage Conditions

Operating Temperature Range	-65 – 125 °C
Environmental Ambient Temperature (Max)	125 °C[257 °F]

Operation/Application

Vibration Resistance	30G's, 10 – 3000Hz
Shock Resistance	75G's, 6ms
Coil Magnetic System	Non-Polarized, Monostable
Current Type	DC

Other

Contact Current Class	≤2 A
Coil Power Rating Class	>.6 – ≤1 W

Product Compliance

For compliance documentation, visit the product page on TE.com>


EU RoHS Directive 2011/65/EU	Not Compliant
EU ELV Directive 2000/53/EC	Out of Scope
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JAN 2025 (247) SVHC > Threshold: Pb (90% in Component Part) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Not lead free process capable

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked.Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles'(Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the

product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

Compatible Parts




TE Part # CAT-3SBH-4PDT-WOCS
4PDT Signal Relay: Electrically-Held, 1 /5-Size Relay




TE Part # CAT-3SBH-4PDT-WCS
4PDT Signal Relay: Electrically-Held, With Coil Suppression

Also in the Series | CII 3SBC Relay



DC Relays(42)



PCB Relays(24)

Customers Also Bought




TE Part #316206-005
55A1121-26-2/6-9




TE Part #5052894108
RNF-100-1/16-BK-SP



TE Part #ZPF000000000007734
983-0SE 28-06 PN-L



TE Part #34319
SPLICE,SOLIS PARA 6



TE Part #205090-2
SKT CONT ASSY,SZ 20,AMPLIMITE

TE Part #1616056-2
A400AA=CONTACTOR-INTERMITTENT



TE Part #3-1617029-3
HFW1131K04M = M39016/6-107M



TE Part #2-1617031-0
HFW1201K45 = M39016/6-109L



TE Part #2-1658012-1
MSB0.80RC-ASY040FL,-,10,-TY



TE Part #1658013-1
MSB0.80PL5ASY040FL,-,10,-TY

Documents

CAD Files

3D PDF

3D

Customer View Model
ENG_CVM_CVM_2-1617072-6_B_c-2-1617072-6-b.2d_dxf.zip

English

Customer View Model
ENG_CVM_CVM_2-1617072-6_B_c-2-1617072-6-b.3d_igs.zip

English

Customer View Model
ENG_CVM_CVM_2-1617072-6_B_c-2-1617072-6-b.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Datasheets & Catalog Pages

RELAY

English