




Connectors > PCB Connectors > Wire-to-Board Connectors > FFC, FPC & Ribbon Connectors > Ribbon Cable Connectors >

AMP-LATCH UNIVERSAL HEADERS



Connector System: **Board-to-Board**  
Number of Positions: **34**  
Centerline (Pitch): **2.54 mm [.1 in]**  
PCB Mount Retention: **Without**  
PCB Mount Retention Type: **Screw Mount**

[All AMP-LATCH UNIVERSAL HEADERS \(497\)](#)

Features

Product Type Features

|                                    |                                |
|------------------------------------|--------------------------------|
| Connector Product Type             | Connector Assembly             |
| Connector Mating Latch & Lock Type | Long                           |
| Ribbon Cable Connector Header Type | Universal Ejection Pin Headers |
| Connector System                   | Board-to-Board                 |
| Connector & Housing Type           | Receptacle                     |
| Connector & Contact Terminates To  | Printed Circuit Board          |

Configuration Features

|                       |          |
|-----------------------|----------|
| Number of Positions   | 34       |
| PCB Mount Orientation | Vertical |
| Number of Rows        | 2        |

Electrical Characteristics

|                       |         |
|-----------------------|---------|
| Operating Voltage     | 250 VAC |
| Insulation Resistance | 5000 MΩ |

Body Features

|                       |         |
|-----------------------|---------|
| Daisy Chain           | Without |
| Primary Product Color | Black   |



|                   |          |
|-------------------|----------|
| Connector Profile | Standard |
|-------------------|----------|

Contact Features

|                                                         |                                                         |
|---------------------------------------------------------|---------------------------------------------------------|
|                                                         | 30 µin                                                  |
| Contact Underplating Material                           | Nickel                                                  |
| Mating Square Post Dimension                            | .64 mm[.025 in]                                         |
| Contact Shape & Form                                    | Square                                                  |
| PCB Contact Termination Area Plating Material Thickness | 2.54 µm[100 µin]                                        |
| Contact Mating Area Plating Material                    | Gold (Au), Gold Flash, Gold Flash over Palladium Nickel |
| PCB Contact Termination Area Plating Material           | Tin-Lead                                                |
| Contact Type                                            | Pin                                                     |
| Contact Current Rating (Max)                            | 1 A                                                     |

Termination Features

|                                  |                       |
|----------------------------------|-----------------------|
| Termination Post & Tail Diameter | .64 mm[.025 in]       |
| Termination Post & Tail Length   | 3.94 mm[.155 in]      |
| Termination Method to PCB        | Through Hole - Solder |

Mechanical Attachment

|                          |                             |
|--------------------------|-----------------------------|
| Panel Mount Feature      | Without                     |
| Mating Alignment         | With                        |
| PCB Mount Alignment      | With                        |
| PCB Mount Retention      | Without                     |
| PCB Mount Retention Type | Screw Mount                 |
| Mating Alignment Type    | Center, Dual Polarizing Bar |
| Mating Retention         | With                        |
| Mating Retention Type    | Ejection Latch              |
| Connector Mounting Type  | Board Mount                 |

Housing Features

|                    |                |
|--------------------|----------------|
| Housing Material   | Thermoplastic  |
| Centerline (Pitch) | 2.54 mm[.1 in] |

Dimensions

|                             |                  |
|-----------------------------|------------------|
| Shrouded End Dimension      | 3.81 mm[.15 in]  |
| PCB Thickness (Recommended) | 3.18 mm[.125 in] |
| Connector Height            | 8.53 mm[.34 in]  |



|                    |                   |
|--------------------|-------------------|
| Connector Length   | 62.48 mm[2.46 in] |
| Row-to-Row Spacing | 2.54 mm[.1 in]    |

Usage Conditions

|                             |                            |
|-----------------------------|----------------------------|
| Housing Temperature Rating  | Standard                   |
| Operating Temperature Range | -65 – 105 °C[-85 – 221 °F] |

Operation/Application

|                        |               |
|------------------------|---------------|
| Solder Process Feature | Solder Dipped |
| Circuit Application    | Signal        |

Industry Standards

|                        |          |
|------------------------|----------|
| UL Flammability Rating | UL 94V-0 |
|------------------------|----------|

Packaging Features

|                    |      |
|--------------------|------|
| Packaging Quantity | 30   |
| Packaging Method   | Tray |

Product Compliance

For compliance documentation, visit the product page on TE.com>

|                                               |                                                                                                                                                                                                                                                                                                                                                                                                                           |
|-----------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EU RoHS Directive 2011/65/EU                  | Not Compliant                                                                                                                                                                                                                                                                                                                                                                                                             |
| EU ELV Directive 2000/53/EC                   | Compliant with Exemptions                                                                                                                                                                                                                                                                                                                                                                                                 |
| China RoHS 2 Directive MIIT Order No 32, 2016 | Restricted Materials Above Threshold                                                                                                                                                                                                                                                                                                                                                                                      |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JUNE 2025 (250)<br>Candidate List Declared Against: JUNE 2025 (250)<br>SVHC > Threshold:<br>Pb (13% in 4690948374)<br><b>Article Safe Usage Statements:</b><br>Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location. |
| Halogen Content                               | Not Low Halogen - contains Br or Cl > 900 ppm.                                                                                                                                                                                                                                                                                                                                                                            |
| Solder Process Capability                     | Wave solder capable to 265°C                                                                                                                                                                                                                                                                                                                                                                                              |

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous



materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 2-1658527-8  
622-3441LF=FSKT IDC S 34 30AU

TE Part # 102320-1  
UNIVERSAL HEADER LATCH

Also in the Series | AMP-LATCH Universal Headers

Connector Hardware(13)

Ribbon Cable Connectors(497)

Customers Also Bought

TE Part #1010-070-0606  
SEAL, INTF, 6P, RED-ORG, SL RET, DT

TE Part #1SNA199635R2400  
FEM13U

TE Part #1SNA199105R2200  
ML10/13.SN

TE Part #1SNA233002R2700  
RC610 1->10 (X10) HORIZONTAL

TE Part #1SNA105004R2200  
M6/8

TE Part #104128-3  
016 LOPRO HDR SP 30DP LATCH

TE Part #350628-1  
.062 COMM P&S SOK 18-24 PTPBR

TE Part #CAT-SCH691-SR1A  
Force Guided Relay with 4 contacts



Documents

Product Drawings

[034 UNIV HDR SP 4S 30DP STD L1](#)

English

CAD Files

[3D PDF](#)

3D

Customer View Model

[ENG\\_CVM\\_CVM\\_102321-8\\_G.2d\\_dxf.zip](#)

English

Customer View Model

[ENG\\_CVM\\_CVM\\_102321-8\\_G.3d\\_igs.zip](#)

English

Customer View Model

[ENG\\_CVM\\_CVM\\_102321-8\\_G.3d\\_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

[Product Specification](#)

English

Instruction Sheets

[Instruction Sheet \(U.S.\)](#)

English

[AMP INSTALLATION PROCEDURES FOR AMP-LATCH UNIVERSAL HEADER ASSEMBLIE](#)

English

Agency Approvals

[Agency Approval Document](#)

English