


**WQV 2.5/30****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Product image**

Screwable cross-connections are easy to mount and de mount. Thanks to the big contact surface, even high currents can be transmitted with maximum contact reliability.

**General ordering data**

|            |                                                                                                                                    |
|------------|------------------------------------------------------------------------------------------------------------------------------------|
| Version    | Cross-connector (terminal), when screwed in, yellow, 32 A, Number of poles: 30, Pitch in mm (P): 5.10, Insulated: Yes, Width: 7 mm |
| Order No.  | <a href="#">1067500000</a>                                                                                                         |
| Type       | WQV 2.5/30                                                                                                                         |
| GTIN (EAN) | 4008190031107                                                                                                                      |
| Qty.       | 10 ST                                                                                                                              |

## Technical data

### Approvals

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

### Dimensions and weights

|            |          |                 |             |
|------------|----------|-----------------|-------------|
| Depth      | 18 mm    | Depth (inches)  | 0.7087 inch |
| Height     | 151.9 mm | Height (inches) | 5.9803 inch |
| Width      | 7 mm     | Width (inches)  | 0.2756 inch |
| Net weight | 22.44 g  |                 |             |

### Temperatures

|                                  |                |                                  |               |
|----------------------------------|----------------|----------------------------------|---------------|
| Storage temperature              | -25 °C...55 °C | Ambient temperature              | -5 °C...40 °C |
| Continuous operating temp., min. | -60 °C         | Continuous operating temp., max. | 130 °C        |

### Environmental Product Compliance

|                        |                             |
|------------------------|-----------------------------|
| RoHS Compliance Status | Compliant without exemption |
| REACH SVHC             | No SVHC above 0.1 wt%       |

### Material data

|                           |       |        |        |
|---------------------------|-------|--------|--------|
| Material                  | PA 66 | Colour | yellow |
| UL 94 flammability rating | V-0   |        |        |

### System specifications

|         |                   |
|---------|-------------------|
| Version | For the terminals |
|---------|-------------------|

### Additional technical data

|                |                 |                     |                 |
|----------------|-----------------|---------------------|-----------------|
| Type of fixing | when screwed in | Installation advice | Direct mounting |
|----------------|-----------------|---------------------|-----------------|

### Cross-connector

|                                          |              |                       |                 |
|------------------------------------------|--------------|-----------------------|-----------------|
| Number of cross-connected terminals      | 30           | Type                  | Cross-connector |
| Tightening torque range for fixing screw | 0.4...0.8 Nm | Rated current, 2-pole | 32 A            |
| Rated current, multi-pole                | 32 A         |                       |                 |

### Dimensions

|                 |         |
|-----------------|---------|
| Pitch in mm (P) | 5.10 mm |
|-----------------|---------|

### General

|                 |    |                     |                 |
|-----------------|----|---------------------|-----------------|
| Number of poles | 30 | Installation advice | Direct mounting |
|-----------------|----|---------------------|-----------------|

### Rating data

|               |      |
|---------------|------|
| Rated current | 32 A |
|---------------|------|

### Classifications

|          |          |          |          |
|----------|----------|----------|----------|
| ETIM 6.0 | EC000489 | ETIM 7.0 | EC000489 |
| ETIM 8.0 | EC000489 | ETIM 9.0 | EC000489 |

### Technical data

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 10.0   | EC000489    | ECLASS 9.0  | 27-14-11-40 |
| ECLASS 9.1  | 27-14-11-40 | ECLASS 10.0 | 27-14-11-40 |
| ECLASS 11.0 | 27-14-11-40 | ECLASS 12.0 | 27-14-11-40 |
| ECLASS 13.0 | 27-25-03-03 | ECLASS 14.0 | 27-25-03-03 |
| ECLASS 15.0 | 27-25-03-03 |             |             |

## Accessories

### Cutting and notching tools for cross-connections



- for Weidmüller Z-Series cross-connections
- for cross-connections from WQV 2.5 to WQV 35
- for cross-connection window of the terminal WSI 6

### General ordering data

|            |                            |                     |  |
|------------|----------------------------|---------------------|--|
| Type       | WAW 1 NEUTRAL              | Version             |  |
| Order No.  | <a href="#">9004500000</a> | Miscellaneous tools |  |
| GTIN (EAN) | 4008190053925              |                     |  |
| Qty.       | 1 ST                       |                     |  |