




Connectors > Terminal Blocks & Strips > Modular Terminal Blocks



Block Function: **Feed-Through & Fuse**

Modular Terminal Block Product Type: **Screw Clamp Terminal Block**

Primary Product Color: **Gray & Dark Gray**

Product Spacing: **8 mm [.315 in]**

Number of Positions: **4**

Features

Product Type Features

Modular Terminal Block Product Type	Screw Clamp Terminal Block
-------------------------------------	----------------------------

Configuration Features

Number of Levels	2
Gauge Type	A3-B3
Number of Circuits	2
Block Function	Feed-Through & Fuse
Number of Positions	4

Electrical Characteristics

Operating Voltage Rating (UL & CSA) (Max) - Main Circuit	300 V
Impulse Withstanding Voltage Rating (IEC)	8000 V
Current Rating (IEC)	6.3 A
Current Rating (UL)	12 A
Current Rating (CSA)	12 A
Dielectric Withstanding Voltage (Max)	2000 V
Voltage Rating (IEC)	800 V
Voltage Rating (CSA)	300 V
Short-Time Withstanding Current Rating @ 1s	480 A

Body Features



Product Weight	29.4 g[1.157 oz]
Primary Product Color	Gray & Dark Gray

Mechanical Attachment

DIN Rail Mounting Type	TH35-15, TH35-7.5
Connector Mounting Type	DIN Rail

Housing Features

Housing Material	Polyamide
------------------	-----------

Dimensions

Product Depth	66.5 mm
Tool Size	3.5 mm[.138 in]
Wire Stripping Length	11 mm[.433 in]
Main Circuit Capacity - 2 Rigid Stranded Conductors per Screw Clamp	24 – 14 AWG
Main Circuit Capacity - Twin Ferrule per Screw Clamp	24 – 14 AWG
Main Circuit Capacity - 2 Flexible Conductors per Screw Clamp	.2 – 2.5 mm²
Main Circuit Capacity - 1 Rigid Stranded Conductor per Screw Clamp	24 – 10 AWG
Main Circuit Capacity - 1 Non-Insulated Ferrule per Screw Clamp	.22 – 4 mm²
Main Circuit Capacity - 1 Insulated Ferrule per Screw Clamp	.22 – 4 mm²
Main Circuit Capacity - 1 Flexible Conductor per Screw Clamp	.22 – 4 mm²
Product Length	66.5 mm
Product Height	89.2 mm
Product Spacing	8 mm[.315 in]

Usage Conditions

Installation Temperature Range	-5 – 40 °C[23 – 104 °F]
Operating Temperature Range	-55 – 110 °C[-67 – 230 °F]

Industry Standards

IP Rating	IP20
UL Flammability Rating	UL 94V-0

Product Compliance

For compliance documentation, visit the product page on [TE.com](#)>

EU RoHS Directive 2011/65/EU	Compliant
------------------------------	-----------



EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	有害物质含量符合标准要求 No Restricted Substance(s) Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>


Compatible Parts



TE Part # 1SNK900611R0000
UMH



TE Part # 1SNK508911R0000
ES4-D2-SF1



TE Part # 1SNA168672R1100
TGA8



TE Part # 1SNK900200R0000
TC5



TE Part # 1SNA173220R0500
PR30



TE Part # 1SNK900104R0000
ES-TC8




TE Part # 1SNK160000R0000
MC812



TE Part # 1SNK900613R0000
PROCAP8



TE Part # 1SNA173523R1100
PC81-10



TE Part # 1SNA168500R1200
PR4



TE Part # 1SNK150000R0000
MC612




TE Part # 1SNK149999R0000
MC512PA




TE Part # 1SNK140000R0000
MC512




TE Part # 1SNK900203R0000
TP2



TE Part # 1SNA178529R0400
PR50



TE Part # 1SNA168673R1200
TGA8




TE Part # 1SNA174300R1700
PR3.Z2



TE Part # 1SNK908302R0000
JB8-2




TE Part # 1SNK159999R0000
MC612PA



TE Part # 1SNK150004R0000
MC612-YL


Also in the Series | ENTRELEC SNK



Modular Terminal Blocks(319)



Terminal Block & Strip Conducting
Accessories(67)



Terminal Block & Strip Insulating
Accessories(31)

Customers Also Bought



TE Part #1SNA233000R0100
RC610



TE Part #1SNA115116R0700
M4/6




TE Part #1SNA173220R0500
PR30




TE Part #1SNA116900R2700
BADH

1SNK508424R0000

Screw Clamp Terminal Block, Feed-Through & Fuse, Gray & Dark Gray, 8 mm [.315 in]
Spacing, 4 Position, DIN Rail, ENTRELEC SNK



TE Part #1SNA115688R2500
[M6/8.SNB](#)



TE Part #1SNA199635R2400
[FEM13U](#)



TE Part #1SNK900001R0000
[BAM4](#)



TE Part #1SNA199168R0000
[ML10/13.SFL](#)



TE Part #CAT-C339-T2201
[Wirewound Resistor: Mineral, 2.5 Kw](#)

Documents

CAD Files

3D PDF

3D

Customer View Model

[ENG_CVM_CVM_1SNK508424R0000_A.2d_dxf.zip](#)

English

Customer View Model

[ENG_CVM_CVM_1SNK508424R0000_A.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_1SNK508424R0000_A.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[ENTRELEC Terminal Block - Master Catalog](#)

[ENTRELEC Terminal Block - Master Catalog](#)

English

[ZS4-D2-SF1-R3](#)

English

[SNK SERIES TERMINAL BLOCKS](#)

English

[ENTRELEC Terminal Blocks Catalogue \(RUS\)](#)

Agency Approvals

[CE Declaration of Conformity](#)

1SNK508424R0000

Screw Clamp Terminal Block, Feed-Through & Fuse, Gray & Dark Gray, 8 mm [.315 in]
Spacing, 4 Position, DIN Rail, ENTRELEC SNK



English