SUNTSU

Multilayer Ceramic Band Pass Filter

SRFBF-7D3F1D-CMBD


7.3mm x 3.5mm

Features

- Miniature Footprint
- Low Insertion Loss
- High Attenuation on Harmonic Suppressed
- LTCC Process

Applications

- 26500-29500MHz Frequency
- 28GHz 5G Network



Part Numbering Guide

S RF BF - 7D3F 1D - CM BD

SUNTSU	RF COMPONENT	BAND PASS FILTER	PACKAGE SIZE*	* INSERT LOSS (dB)	APPLICATION	FREQUENCY BAND
			7D3F = 7.3mm x 3.5mm	1D = 1.3dB	CM = Combo	BD : 26500-29500


RoHS COMPLIANT

* Where letters denote decimal location (A=.0, B=.1, C=.2, etc.); e.g. B5=0.15, 3A5=3.05, 9A=9.0

Electrical Parameters	Units	Minimum	Typical	Maximum	Remarks
Frequency	MHz	26500		29500	
Insertion Loss @ 25°C	dB			1.5	
Return Loss	dB	10			
Impedance	Ω		50		
Operating Temperature Range	°C	-40		85	
Storage Temperature Range	°C	-40		85	
Attenuation @24000MHz	dB	20			

Outline Drawing

All dimensions are in millimeters (mm) unless otherwise noted. Drawings are not to scale.



PIN	FUNCTION
1	Input
2	Output
3	GND

Suntsu Electronics, Inc.
142 TECHNOLOGY DR., SUITE 150
IRVINE, CA 92618

Call: +1-949-783-7300 | Fax: +1-949-783-7301


SUNTSU

Multilayer Ceramic Band Pass Filter

SRFBF-7D3F1D-CMBD


7.3mm x 3.5mm

Typical Electrical Chart




Land Pattern

All dimensions are in millimeters (mm) unless otherwise noted.
Drawings are not to scale.




Line width to be designed to match 50Ω characeristic impedance, depending on PCB material and thickness.

Test Circuit




Reflow Profile




Tape and Reel Dimensions

All dimensions are in millimeters (mm) unless otherwise noted.
Drawings are not to scale.

3,000 pcs/reel



Markings



Suntsu Electronics, Inc.
142 TECHNOLOGY DR., SUITE 150
IRVINE, CA 92618

Call: +1-949-783-7300 | Fax: +1-949-783-7301

SUNTSU

Multilayer Ceramic Band Pass Filter

SRFBF-7D3F1D-CMBD

7.3mm x 3.5mm

Reliability Test		
Test Item	Test Conditions/Test Method	Specification
Solderability **JIS C 0050-4.6** **JESD22-B1D**	*Solder bath temperature : 235±5°C *Immersion time : 2±0.5 sec Solder : Sn^3Ag 0.5Cu for lead-free	At least 95% of a surface of each terminal electrode must be covered by fresh solder.
Leaching (Resistance to dissolution of metallization) **IEC 60068-2-58**	*Solder bath temperature : 260±5°C *Leaching immersion time : 30±0.5 sec Solder : SN63A	Loss of metallization on the edges of each electrode shall not exceed 25%
Resistance to soldering heat **JIS C 0050-5.4**	*Preheating temperature : 120~150°C, 1 minute *Solder temperature : 270±5°C *Immersion time : 10±1 sec Solder : Sn3Ag 0.5Cu for lead-free Measurement to be made after keeping at room temperature for 24±2 hrs.	No mechanical damage. Eletrical specification shall satisfy the descriptions in electrical characteristics under the operational temperature ranger within -40~85°C. Loss of metallization on the edges of each electrode shall not exceed 25%
Drop Test **JIS C 0044**	*Height : 75 cm *Test surface : Rigid surface of concrete or steel. *Times : 6 surfaces for each unit; 2 times each side.	No mechanical damage. Electrical specification shall satisfy the description in electrical characteristics under the operational temperature range within -40~85°C.
Vibration **JIS C 0040**	*Frequency : 10Hz~55Hz~10Hz (1 min) *Total amplitude : 1.5mm *Test times : 6hrs (two hrs each in three mutually perpendicular directions)	No mechanical damage. Eletrical specification shall satisfy the descriptions in electrical characteristics under the operational temperature range within -40~85°C.
Adhesive Strength of Termination **JIS C 0051-7.4.3**	*Pressurizing force : 5N(≤603) ; 10N(>0603) *Test time : 10±1 sec	No remarkable damage or removal of the termination
Bending Test **JIS C 0051-7.4.1**	The middle part of substrate shall be pressurized by means of the pressurizing rod at a rate of about 1mm/s per second until the deflection becomes 1mm/s and then pressure shall be maintained for 5±1 sec. Measurement to be made after keeping at room temperature for 24±2 hours.	No mechanical damage. Eletrical specification shall satisfy the descriptions in electrical characteristics under the operational temperature range within -40~85°C.
Temperature Cycle **JIS C 0025**	1. 30±3 minutes at -40°C±3°C 2. 10~15 minutes at room temperature 3. 30±3 minutes at 85°C±3°C 4. 10~15 minutes at room temperaure Total 100 continuous cycles Measurement to be made after keeping at room temperature for 24±2 hous.	No mechanical damage. Eletrical specification shall satisfy the descriptions in electrical characteristics under the operational temperature range within -40~85°C.
High Temperature **JIS C 0021**	*Temperature : 85°C±2°C *Test duration : 1000+24/-0 hours Measurement to be made after keeping at room temperature for 24±2 hours.	No mechanical damage. Eletrical specification shall satisfy the descriptions in electrical characteristics under the operational temperature range within -40~85°C.
Humidity (steady conditions) **JIS C 0022**	*Humidity : 90% to 95% Relative Humidity *Temperature : 40°C±2°C *Time : 1000+24/-0 hours Measurement to be made after keeping at room temperature for 24±2 hours. **500hrs measuring the first data then 1000hrs data	No mechanical damage. Eletrical specification shall satisfy the descriptions in electrical characteristics under the operational temperature range within -40~85°C.
Low Temperature **JIS C 0020**	*Temperature : -40°C±2°C *Test duration : 1000+24/-0 hours Measurement to be made after keeping at room temperature for 24±2 hours.	No mechanical damage. Eletrical specification shall satisfy the descriptions in electrical characteristics under the operational temperature range within -40~85°C.

Suntsu Electronics, Inc.
142 TECHNOLOGY DR., SUITE 150
IRVINE, CA 92618

Call: +1-949-783-7300 | Fax: +1-949-783-7301