Aug.1.2025 Copyright 2025 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

| APPLICABLE STANDARD | | | | |
|---|---|---|---|---|
| RATING | OPERATING TEMPERATURE RANGE | -35 °C TO +85 °C(NOTES 1) | STORAGE TEMPERATURE RANGE | -10 °C TO +60 °C |
| | VOLTAGE | 250 V AC | APPLICABLE CONNECTOR | DF1E(A)-*EP-2.5C |
| | CURRENT | AWG28 TO 24: 1 TO 3A | APPLICABLE CABLE | UL1007, 1061: AWG28 TO 24 |

# SPECIFICATIONS

| ITEM | TEST METHOD | REQUIREMENTS | QT | AT |
|---|---|---|---|---|
| **CONSTRUCTION** | | | | |
| GENERAL EXAMINATION | VISUALLY AND BY MEASURING INSTRUMENT. | ACCORDING TO DRAWING. | X | X |
| MARKING | CONFIRMED VISUALLY. | | X | X |
| **ELECTRIC CHARACTERISTICS** | | | | |
| CONTACT RESISTANCE | 20 mV MAX. 1 mA (DC OR 1000 Hz). | 30 mΩ MAX. | X | – |
| **MECHANICAL CHARACTERISTICS** | | | | |
| MECHANICAL OPERATION | 30 TIMES INSERTIONS AND EXTRACTIONS. | ① CONTACT RESISTANCE: 30 mΩ MAX.<br>② NO DAMAGE, CRACK OR LOOSENESS OF PARTS. | X | – |
| VIBRATION | FREQUENCY 10 TO 55 Hz, SINGLE AMPLITUDE 0.75 mm, AT 2 h, FOR 3 DIRECTIONS. | ① NO ELECTRICAL DISCONTINUITY OF 1 μs.<br>② NO DAMAGE, CRACK OR LOOSENESS OF PARTS. | X | – |
| SHOCK | 490 $m/s^2$ DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS. | | X | – |
| **ENVIRONMENTAL CHARACTERISTICS** | | | | |
| RAPID CHANGE OF TEMPERATURE | TEMPERATURE -55→ 5 TO 35→+85→ 5 TO 35 °C<br>TIME 30→ 5 MAX → 30→ 5 MAX min<br>UNDER 5 CYCLES. | ① CONTACT RESISTANCE: 30 mΩ MAX.<br>② NO DAMAGE, CRACK OR LOOSENESS OF PARTS. | X | – |
| DAMP HEAT (STEADY STATE) | EXPOSED AT 40 ± 2 °C, 90 TO 95 %, 96 h. | | X | – |

| | COUNT | DESCRIPTION OF REVISIONS | DESIGNED | CHECKED | DATE |
|---|---|---|---|---|---|
| ⚠0 | | | | | |

REMARKS
NOTE1: INCLUDE THE TEMPERATURE RISING BY CURRENT

Unless otherwise specified, refer to JIS C 5402.

| | | |
|---|---|---|
| APPROVED | TY.OMA | 07.03.20 |
| CHECKED | HK.UMEHARA | 07.03.20 |
| DESIGNED | TS.FUKUSHIMA | 07.03.19 |
| DRAWN | TS.FUKUSHIMA | 07.03.19 |

Note QT:Qualification Test AT:Assurance Test X:Applicable Test

DRAWING NO. ELC4-161022-01

HRS

SPECIFICATION SHEET

HIROSE ELECTRIC CO., LTD.

PART NO. DF1E-2428PCF

CODE NO. CL541-0939-3-00 ⚠0



FORM HD0011-2-1