




Connectors > Terminal Blocks & Strips > Modular Terminal Blocks



Block Function: **Feed-Through**
Modular Terminal Block Product Type: **Screw Clamp Terminal Block**
Primary Product Color: **Gray**
Product Spacing: **16 mm [.63 in]**
Number of Positions: **2**

Features

Product Type Features

Modular Terminal Block Product Type	Screw Clamp Terminal Block
-------------------------------------	----------------------------

Configuration Features

Number of Levels	1
Gauge Type	Dia.11
Number of Circuits	1
Block Function	Feed-Through
Number of Positions	2

Electrical Characteristics

Power Loss	4.8 W
Operating Voltage Rating (UL & CSA) (Max) - Main Circuit	1000 V
Impulse Withstanding Voltage Rating (IEC)	8000 V
Current Rating (IEC)	150 A
Current Rating (UL)	140 A
Current Rating (CSA)	140 A



Dielectric Withstanding Voltage (Max)	2200 V
Voltage Rating (IEC)	1000 V
Voltage Rating (CSA)	1000 V
Short-Time Withstanding Current Rating @ 1s	6000 A
Operating Voltage	1000 VAC

Body Features

Product Weight	52.9 g[2.083 oz]
Primary Product Color	Gray

Termination Features

Termination Method to Wire & Cable	Screw Terminal
------------------------------------	----------------

Mechanical Attachment

DIN Rail Mounting Type	TH35-15, TH35-7.5
Connector Mounting Type	DIN Rail

Housing Features

Housing Material	Polyamide
------------------	-----------

Dimensions

Product Depth	60.2 mm[2.37 in]
Wire Stripping Length	17 mm[.669 in]
Main Circuit Capacity - 2 Rigid Stranded Conductors per Screw Clamp	18 – 4 AWG
Main Circuit Capacity - Twin Ferrule per Screw Clamp	18 – 4 AWG
Main Circuit Capacity - 2 Flexible Conductors per Screw Clamp	1 – 25 mm²
Main Circuit Capacity - 1 Rigid Stranded Conductor per Screw Clamp	18 AWG
Main Circuit Capacity - 1 Non-Insulated Ferrule per Screw Clamp	1 – 50 mm²
Main Circuit Capacity - 1 Insulated Ferrule per Screw Clamp	1 – 50 mm²
Main Circuit Capacity - 1 Flexible Conductor per Screw Clamp	1 – 50 mm²
Product Height	63.6 mm[2.504 in]
Product Spacing	16 mm[.63 in]
Wire Size	1 AWG

Usage Conditions

Installation Temperature Range	-5 – 40 °C[23 – 104 °F]
Operating Temperature Range	-55 – 110 °C[-67 – 230 °F]



Operation/Application

Circuit Application	Power & Signal
---------------------	----------------

Industry Standards

UL Flammability Rating	UL 94V-0
------------------------	----------

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	有害物质含量符合标准要求 No Restricted Substance(s) Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability


Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts




TE Part # 1SNK140000R0000
[MC512](#)



TE Part # 1SNA178529R0400
[PR50](#)




TE Part # 1SNK916310R0000
[JB16-10](#)




TE Part # 1SNA174300R1700
[PR3.Z2](#)




TE Part # 1SNK159999R0000
[MC612PA](#)




TE Part # 1SNK150004R0000
[MC612-YL](#)



TE Part # 1SNK916302R0000
[JB16-2](#)




TE Part # 1SNK140004R0000
[MC512-YL](#)




TE Part # 1SNK916304R0000
[JB16-4](#)



TE Part # 1SNK900611R0000
[UMH](#)



TE Part # 1SNK916305R0000
[JB16-5](#)




TE Part # 1SNA173220R0500
[PR30](#)




TE Part # 1SNK900102R0000
[BAZH1](#)




TE Part # 1SNK169999R0000
[MC812PA](#)




TE Part # 1SNA164800R0300
[PR3.G2](#)




TE Part # 1SNK160004R0000
[MC812-YL](#)



TE Part # 1SNA168700R2200
[PR5](#)



TE Part # 1SNK916303R0000
[JB16-3](#)




TE Part # 1SNK160000R0000
[MC812](#)



TE Part # 1SNK900613R0000
[PROCAP8](#)


Also in the Series | [ENTRELEC SNK](#)



Modular Terminal Blocks(319)



Terminal Block & Strip Conducting Accessories(67)



Terminal Block & Strip Insulating Accessories(31)

Customers Also Bought



TE Part #1SNK516064R0000
ZS50-BK



TE Part #1SNK516010R0000
ZS35



TE Part #1SNA115236R1700
M6/8.ST



TE Part #1SNK505010R0000
ZS4



TE Part #1SNK516020R0000
ZS35-BL




TE Part #1SNK510010R0000
ZS16




TE Part #1SNK505210R0000
ZS4-D2



TE Part #1SNK506010R0000
ZS6



TE Part #1SNA115281R1500
M4/6.5.3G



TE Part #1SNA195639R2400
M6/8.ST1.V0.IP20

Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1SNK516011R0000_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1SNK516011R0000_A.3d_igs.zip

1SNK516011R0000

Screw Clamp Terminal Block, Feed-Through, Gray, 16 mm [.63 in] Spacing, 2 Position, Screw Terminal, Power & Signal, DIN Rail, 1000 VAC, ENTRELEC SNK



English

Customer View Model

ENG_CVM_CVM_1SNK516011R0000_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

ZS50

English

ENTRELEC Terminal Block - Master Catalog

ENTRELEC Terminal Block - Master Catalog

English

SNK SERIES TERMINAL BLOCKS

English

ENTRELEC Terminal Blocks Catalogue (RUS)

Essential Entrelec Terminal Blocks

French

Essential Entrelec Terminal Blocks

English

Essential Entrelec Terminal Blocks

Japanese

Agency Approvals

ZK-ZS_ATEX_1SND225112U1006-C-TE

English