61281-3 ✔ ACTIVE

FASTON | FASTON 250

TE Internal #: 61281-3

Quick Disconnect Tab, Uninsulated, 14 – 12 AWG, 2.1 – 3.31 mm² Wire, 6.35 mm [.25 in] Tab Width, F-Crimp, Straight, Brass, Tin Plating, FASTON 250

View on TE.com >

Terminals & Splices > Quick Disconnects

Quick Disconnect Terminal Type: **Tab**

Wire Size: **2.1 – 3.31 mm²**

Mating Tab Width: **6.35 mm [.25 in]**

Mating Tab Thickness: **.81 mm [.032 in]**

Features

Product Type Features

Insertion Force	Normal

Configuration Features

Compatible With Wire & Cable Type	Discrete Wire
Connection Capacity	Single

Contact Features

Quick Disconnect Terminal Type	Tab
Mating Tab Width	6.35 mm[.25 in]
Mating Tab Thickness	.81 mm[.032 in]
Terminal Orientation	Straight
Contact Base Material	Brass
Terminal Plating Material	Tin
Crimp Type	F-Crimp
Barrel Type	Open

Termination Features

Product Terminates To	Wire & Cable

Mechanical Attachment

Wire Insulation Support	With
Mating Retention Type	Dimple

Dimensions

Product Length	20.57 mm[.81 in]
Compatible Insulation Diameter Range	2.79 – 4.32 mm[.11 – .17 in]
Terminal Material Thickness	.4 mm[.015 in]
Wire Size	2.1 – 3.31 mm²

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 110 °C[-40 – 230 °F]

Industry Standards

Compatible With Agency/Standards Products	CSA, UL

Packaging Features

Packaging Quantity	3000
Packaging Method	Strip/Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



TE Part # 7-2151771-7
OCEAN_2.0_SPARE_PART_KIT-120F180F

TE Part # 2151771-2
OCEAN_2.0_Applicator-S-120F180F-RSA

TE Part # 2305570-1
Strip Terminal Cutter-Side Feed-No Crimp

TE Part # 180353-2
250 FASTON,TAB,12-10 AWG,TPBR

TE Part # 1494210-2
110 FASTON,TAB,22-17 AWG, JIS C260

TE Part # 2151771-1
OCEAN_2.0_Applicator-S-120F180F-RSM

TE Part # 1494210-1
110 FASTON,TAB,22-17 AWG, JIS C260

TE Part # 180353-1
250 FASTON,TAB,12-10 AWG,BR



TE Part # 60794-2
FASTIN NECESSARY?? - separate GPL: 326

TE Part # 63165-2
FASTON 110 AMPLIVAR TAB 23-19 MAG TPBR

Also in the Series | FASTON 250

Compression Connectors(4)



Crimp Terminal Housings(115)

Insulation Boots & Sleeves(16)



Magnet Wire Terminals(1)

PCB Terminals(133)

Quick Disconnects(412)

Splices(4)

Customers Also Bought

TE Part #2056350005
ES-CAP-NO.3-B8-0-40MM

TE Part #60197-1
110 FASTON REC 22-18 AWG TPBR



TE Part #62428-2
250 FASTON REC 12-10 AWG TPBR

TE Part #2-1419158-5
GET MALE TERM, B, SN, REREEL

TE Part #1-1969543-0
ASSY, HDR, VERT, 10P, DUAL ROW, EP2.5

TE Part #1-1969543-4
ASSY, HDR, VERT, BOSSED, DUAL ROW, EP2.5

TE Part #2098762-1
Contact,female0.64, 20-22AWG,



TE Part #2404280-8
EP 2.5 HDR, GLOW WIRE, 8P

TE Part #2407489-3
3P, RAST 5 HEADER, DIN, SILVER, SHROUDED

TE Part #1-2355813-3
3P, RAST5 POTTED HEADER DIN, SILVER, SL

Documents

Product Drawings

250 FASTON TAB 14-12 AWG TPBR

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_61281-3_V.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_61281-3_V.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_61281-3_V.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Datasheets & Catalog Pages

FASTON Tabs

English

Product Specifications

EB**General Application Specification for Open Barrel Terminals

English

Application Specification

English

Application Specification

English

Agency Approvals

CSA Certificate

English

CSA Certificate

English