# Branching module
# MS4-FRM-1/4

Part number: 529555



General operating condition

## Data sheet

| Feature | Value |
|---|---|
| Mounting position | Any |
| Structural design | Branching module |
| Symbol | 00991510 |
| Operating pressure | 0 bar ... 14 bar |
| Standard nominal flow rate in main flow direction 1 -> 2 | 4600 l/min |
| Standard nominal flow rate outlet at top | 1500 l/min |
| Standard nominal flow rate outlet down | 1500 l/min |
| Operating medium | Compressed air as per ISO 8573-1:2010 [7:4:4]<br>Inert gas |
| Information on operating and pilot media | Operation with oil lubrication possible (required for further use) |
| Corrosion resistance class (CRC) | 2 - Moderate corrosion stress |
| LABS (PWIS) conformity | VDMA24364-B1/B2-L |
| Storage temperature | -10 °C ... 60 °C |
| For use in the food industry | See supplementary material information |
| Temperature of medium | -10 °C ... 60 °C |
| Ambient temperature | -10 °C ... 60 °C |
| Product weight | 165 g |
| Pneumatic connection 1 | G1/4 |
| Pneumatic connection 2 | G¼ |
| Pneumatic connection 3 | G1/4 |
| Pneumatic connection 4 | G1/4 |
| Note on materials | RoHS-compliant |
| Housing material | Die-cast aluminum |