

Data sheet | Item number: 285-421

Finger guard; touchproof cover protects unused conductor entries; for 35 mm² high-current tbs; yellow

www.wago.com/285-421



Data
Material data

Note (material data)

Information on material specifications can be found [here](#)

Color	yellow
Material group	I
Insulation material	Polyamide (PA66)
Flammability class per UL94	V0
Fire load	0.021 MJ
Weight	0.7 g

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Commercial data

Product Group	1 (Rail Mounted Terminal Blocks)
eCl@ss 10.0	27-14-11-92
eCl@ss 9.0	27-14-11-92
ETIM 8.0	EC002848
ETIM 7.0	EC002848
ECCN	NO DATA
PU (SPU)	100 (25) pcs
Packaging type	box
Country of origin	DE
GTIN	4066966346435
Customs tariff number	39269097900

Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Downloads

Documentation

Bid Text

285-421 X81 - Datei	2019 年2月19 日	xml 2.7 kB	Download
285-421 doc - Datei	2017 年2月27 日	doc 23.0 kB	Download

Additional Information

Technical Section Technical explanations	pdf 2.3 MB	Download
---	---------------	----------

CAD/CAE-Data

CAE data

WSCAD Universe 285-421	URL	Download
ZUKEN Portal 285-421	URL	Download

EPLAN Data Portal 285-421

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



	URL	Download
CAD data		
2D/3D Models 285-421	URL	Download
Asset Administration Shell		
Asset Administration Shell 285-421	URL	Download

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 285-421	URL	Download
Finger guard; touchproof cover protects unused conductor entries; for 35 mm² high-current tbs; yellow		

Installation Notes

Subject to changes. Please also observe the further product documentation!