Part Number : 2151130001

Product Description : Sentrality 6.0mm Top-entry, Eye-of-Needle Press-fit Socket Assembly with +/- 1.00mm Self-alignment Capability, Tray

Series Number : 215113

Status : Active

Product Category : PCB Headers and Receptacles

Documents & Resources

Drawings

Drawing 2151130001_sd.pdf

Packaging Design Drawing 2151130000-PK-000.pdf

3D Models and Design Files

3D Model 2151130001_stp.zip

Specifications

Application Specification 2151130000-AS-000.pdf

Product Specification 2151130000-PS-000.pdf

Test Summary 2043131234-TS-000.pdf

Test Summary 2151130000-TS-000.pdf

Product Environment Compliance

Compliance

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2023)8585-DC (23 Jan 2024)
EU RoHS	Compliant per EU 2015/863

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

Status	Active
Category	PCB Headers and Receptacles
Series	215113
Description	Sentrality 6.0mm Top-entry, Eye-of-Needle Press-fit Socket Assembly with +/- 1.00mm Self-alignment Capability, Tray
Application	Board-to-Board, Busbar-to-Board, Power
Comments	Current and voltage performances are dependent upon application variables.
Component Type	PCB Receptacle
Product Family	Sentrality Pin and Socket Interconnect System
Product Name	Sentrality
UPC	193264760411

Agency

CSA	LR19980
UL	E29179

Electrical

Current - Maximum per Contact	140.0A
Voltage - Maximum	600V

Physical

Circuits (Loaded)	1
Circuits (maximum)	1

Diameter	6.00mm
Durability (mating cycles max)	200
Glow-Wire Capable	No
Guide to Mating Part	Yes
Height Above Board	11.84mm
Material - Metal	Copper Alloy
Material - Plating Mating	Gold
Material - Plating Termination	Silver
Mating Orientation	Top-entry
Net Weight	11.801/g
Number of Rows	1
Orientation	Vertical
Packaging Type	Tray
PCB Retention	None
Pitch - Mating Interface	N/A
Polarized to PCB	No
Temperature Range - Operating	-40° to +125°C
Termination Interface Style	Through Hole - Compliant Pin

Mates With / Use With

Mates with Part(s)

Description	Part Number
Sentrality Pins	203263