Data sheet



WTT4SLC-3B2262B09

WTT4 PowerProx

TIME-OF-FLIGHT SENSORS

SICK
Sensor Intelligence.



Illustration may differ

Ordering information

Type	part no.
WTT4SLC-3B2262B09	1143216

Other models and accessories → www.sick.com/WTT4_PowerProx

Detailed technical data

Features

Functional principle	Photoelectric proximity sensor
Functional principle detail	Background suppression, Optical time-of-flight
Housing design (light emission)	Rectangular
Sensing range max.	50 mm ... 1,300 mm [1]
Sensing range	100 mm ... 1,300 mm [2]
Distance value	
Measuring range	90 mm ... 1,300 mm [1]
Resolution	1 mm
Repeatability	4,5 mm ... 11 mm [3] [4] [5]
Accuracy	- 10 mm, + 80 mm
Distance value output	Via IO-Link
Update rate of the distance value	0.8 ms
Type of light	Visible red light
Light source	Laser [6]
Light spot size (distance)	Ø 4 mm (1,000 mm)

[1] Object with 6 ... 90% remission (based on standard white, DIN 5033).
[2] Adjustable.
[3] Equivalent to 1 σ.
[4] See characteristic curves repeatability.
[5] 6% ... 90% remission factor.
[6] Average service life: 50,000 h at T_U = +25 °C.

Wave length	658 nm
Laser class	1 (IEC 60825-1 / CDRH 21 CFR 1040.10 & 1040.11)
Adjustment	Single teach-in button, Teach-in input, IO-Link
Pin 2 configuration	Pin2 pre-setting (MF): teach-in via cable
Safety-related parameters	
$MTTF_D$	256 years
DC_{avg}	0 %
T_M (mission time)	20 years

[1] Object with 6 ... 90% remission (based on standard white, DIN 5033).
[2] Adjustable.
[3] Equivalent to 1 σ.
[4] See characteristic curves repeatability.
[5] 6% ... 90% remission factor.
[6] Average service life: 50,000 h at T_U = +25 °C.

Interfaces

Communication interface	IO-Link V1.1
Communication Interface detail	COM3 (230,4 kBaud)
Cycle time	0.8 ms
Process data length	4 Byte
Process data structure	Bit 0 = switching signal Q_{L1} Bit 1 = switching signal Q_{L2} Bit 2 = detection signal Qint.1 Bit 3 = detection signal Qint.2 Bit 4 = detection signal Qint.3 Bit 5 = detection signal Qint.4 Bit 6 = detection signal Qint.5 Bit 7 = detection signal Qint.6 Bit 8 = detection signal Qint.7 Bit 9 = detection signal Qint.8 Bit 10 ... 15 = empty Bit 16 ... 31 = distance value
VendorID	26
DeviceID HEX	0x80037C
DeviceID DEC	8389500

Electronics

Supply voltage U_B	10 V DC ... 30 V DC [1]
Ripple	< 5 V_{pp} [2]
Current consumption	25 mA [3]
Switching output	Push-pull: PNP/NPN

[1] Limit values. Operated in short-circuit protected network: max. 8 A.
[2] May not fall below or exceed U_V tolerances.
[3] Without load.
[4] Signal transit time with resistive load.
[5] With light/dark ratio 1:1.
[6] A = V_S connections reverse-polarity protected.
[7] B = output reverse-polarity protected.
[8] D = outputs overcurrent and short-circuit protected.
[9] Below T_u = –10 °C a warm-up time is necessary.

Output function	Factory setting: Pin 2 / white (MF): NPN normally open (light switching), PNP normally closed (dark switching), Pin 4 / black (QL1 / C): NPN normally closed (dark switching), PNP normally open (light switching), IO-Link
Switching mode	Light/dark switching
Output current $I_{max.}$	≤ 50 mA
Response time	≤ 5 ms [4]
Switching frequency	100 Hz [5]
Input	MF_{in} = multifunctional input programmable
Circuit protection	A [6] B [7] D [8]
Protection class	III
Enclosure rating	IP67
Warm-up time	< 10 min [9]
Initialization time	< 300 ms

[1] Limit values. Operated in short-circuit protected network: max. 8 A.
[2] May not fall below or exceed U_V tolerances.
[3] Without load.
[4] Signal transit time with resistive load.
[5] With light/dark ratio 1:1.
[6] A = V_S connections reverse-polarity protected.
[7] B = output reverse-polarity protected.
[8] D = outputs overcurrent and short-circuit protected.
[9] Below T_u = –10 °C a warm-up time is necessary.

Mechanics

Dimensions (W x H x D)	12.2 mm x 41.8 mm x 17.3 mm
Housing material	Plastic, MABS, ABS
Optics material	Plastic, PMMA
Weight	10 g
Connection type	Male connector M8, 4-pin

Ambient data

Ambient operating temperature	–40 °C ... +50 °C [1]
Ambient temperature, storage	–40 °C ... +75 °C

[1] As of T_a = 45 °C, a max.load current I_{max} = 50 mA is permitted.

Smart Task

Smart Task name	Base logics
Logic function	Direct AND OR WINDOW Hysteresis
Timer function	Deactivated Switch-on delay Off delay ON and OFF delay Impulse (one shot)

Inverter	Yes
Switching signal	
Switching signal Q_{L1}	Switching output
Switching signal Q_{L2}	Switching output


Certificates

EU declaration of conformity	✓
UK declaration of conformity	✓
ACMA declaration of conformity	✓
Moroccan declaration of conformity	✓
China-RoHS	✓
cULus certificate	✓
IO-Link	✓
Laser safety (IEC 60825-1) certificate	✓

Classifications


ECLASS 5.0	27270904
ECLASS 5.1.4	27270904
ECLASS 6.0	27270904
ECLASS 6.2	27270904
ECLASS 7.0	27270904
ECLASS 8.0	27270904
ECLASS 8.1	27270904
ECLASS 9.0	27270904
ECLASS 10.0	27270904
ECLASS 11.0	27270904
ECLASS 12.0	27270903
ETIM 5.0	EC002719
ETIM 6.0	EC002719
ETIM 7.0	EC002719
ETIM 8.0	EC002719
UNSPSC 16.0901	39121528

Dimensional drawing




Dimensions in mm (inch)
① Center of optical axis
② Connection
③ LED indicator green: power
④ LED indicator yellow: Status of received light beam
⑤ single teach-in button
⑥ Threaded mounting hole M3

Connection diagram Cd-367




Light spot size




① Light spot horizontal
② Light spot vertical

Scanning range




① 6 % / 90 % AVG1
② 6 % / 90 % AVG2
③ 6 % / 90 % AVG4
④ 6 % / 90 % AVG8
⑤ 6 % / 90 % AVG64
⑥ 6 % / 90 % AVG512

Scanning range



① 90 % / 90 % AVG1
② 90 % / 90 % AVG2
③ 90 % / 90 % AVG4
④ 90 % / 90 % AVG8
⑤ 90 % / 90 % AVG64
⑥ 90 % / 90 % AVG512

Repeatability



① 6 % remission, on black
② 90 % remission, on white

Recommended accessories

Other models and accessories ➜ www.sick.com/WTT4_PowerProx

	Brief description	Type	part no.
Mounting systems			
	• **Description:** Plate N08N for universal clamp bracket • **Material:** Stainless steel, stainless steel • **Details:** Stainless steel 1.4571 (sheet), Stainless steel 1.4408 (clamp) • **Items supplied:** Universal clamp (5322627), mounting hardware • **Usable for:** W100, W150, W4-3, W4S-3, W8, W9-3, W8G, W8 Laser, W8 Inox, G6, W100 Laser, W100-2, W4-3 Glass, W4S-3 Glass, RAY10, W4SLG-3, W9, GR18, MultiPulse, Reflex Array, Multi-Line, LUT3, KT5, KT8, KT10, CS8, G6 Inox	BEF-KHS-N08N	2051616

SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is “Sensor Intelligence.”

WORLDWIDE PRESENCE:

Contacts and other locations –www.sick.com