



Color: ■ orange Similar to illustration

Electrical data

Ratings per IEC/EN	
Nominal voltage (III/3)	500 V
Rated current	30 A

Physical data

Width	39.2 mm / 1.543 inches
Depth	13 mm / 0.512 inches
Jumper assignment	1-2-3-4-5

Material data

Note (material data)	
Information on material specifications can be found here	
Color	orange
Fire load	0.031 MJ
Weight	5.2 g

Environmental requirements

Environmental Testing (Environmental Conditions)		Environmental Testing (Environmental Conditions)	
Test specification Railway applications – Rolling stock – Electronic equipment	DIN EN 50155 (VDE 0115-200):2022-06	Test duration per axis	10 min. 5 h
Test procedure Railway applications – Rolling stock equipment – Shock and vibration tests	DIN EN 61373 (VDE 0115-0106):2011-04	Test directions	X, Y and Z axes X, Y and Z axes X, Y and Z axes
Spectrum/Installation location	Service life test, Category 1, Class A/B	Monitoring for contact faults/interruptions	Passed
Function test with noise-like vibration	Test passed according to Section 8 of the standard	Voltage drop measurement before and after each axis	Passed
Frequency	f ₁ = 5 Hz to f ₂ = 150 Hz f ₁ = 5 Hz to f ₂ = 150 Hz	Simulated service life test through increased levels of noise-like vibration	Test passed according to Section 9 of the standard
Acceleration	0.101g (highest test level used for all axes) 0.572g (highest test level used for all axes) 5g (highest test level used for all axes)	Extended test scope: Monitoring for contact faults/interruptions	Passed Passed
		Extended test scope: Voltage drop measurement before and after each axis	Passed Passed
		Shock test	Test passed according to Section 10 of the standard



Environmental Testing (Environmental Conditions)	
Shock form	Half sine
Shock duration	30 ms
Number of shocks per axis	3 pos. und 3 neg.
Vibration and shock stress for rolling stock equipment	Passed

Commercial data	
Product Group	22 (TOPJOB S)
PU (SPU)	50 (10) pcs
Packaging type	Box
Country of origin	DE
GTIN	4050821458432
Customs tariff number	85366990990

Product classification	
UNSPSC	39121421

Environmental Product Compliance	
RoHS Compliance Status	Compliant,No Exemption

Approvals / Certificates

Declarations of conformity and manufacturer's declarations



Approval	Standard	Certificate Name
Railway WAGO GmbH & Co. KG	-	Railway Ready

Downloads

Environmental Product Compliance	
Compliance Search	
Environmental Product Compliance 2007-8445	

Documentation

Bid Text			
2007-8445	28.04.2017	doc 23.00 KB	
2007-8445	19.02.2019	xml 2.52 KB	

CAD/CAE-Data	
CAD data 2D/3D Models 2007-8445 ↓	CAE data EPLAN Data Portal 2007-8445 ↓
	WSCAD Universe 2007-8445 ↓
	ZUKEN Portal 2007-8445 ↓

Installation Notes

Commoning



Preparing shorting path for the current transformer circuits.

Insert insulated, touch-proof circuit jumpers into jumper slot.

Insert insulated, touch-proof circuit jumpers into jumper slot.