




Connectors > Terminal Blocks & Strips > Modular Terminal Blocks



Block Function: **Fuse**

Modular Terminal Block Product Type: **Screw Clamp Terminal Block**

Primary Product Color: **Gray & Dark Gray**

Product Spacing: **8 mm [.315 in]**

Number of Positions: **2**

Features

Product Type Features

Modular Terminal Block Product Type	Screw Clamp Terminal Block
-------------------------------------	----------------------------

Configuration Features

Number of Levels	1
Gauge Type	A3-B3
Number of Circuits	1
Block Function	Fuse
Number of Positions	2

Electrical Characteristics

Operating Voltage Rating (UL & CSA) (Max) - Main Circuit	300 V
Impulse Withstanding Voltage Rating (IEC)	8000 V
Current Rating (IEC)	6.3 A
Current Rating (UL)	10 A
Current Rating (CSA)	6.3 A
Dielectric Withstanding Voltage (Max)	2200 V
Voltage Rating (IEC)	630 V
Voltage Rating (CSA)	300 V

Body Features

--	--



Product Weight	13.3 g[.524 oz]
Primary Product Color	Gray & Dark Gray

Mechanical Attachment

DIN Rail Mounting Type	TH35-15, TH35-7.5
Connector Mounting Type	DIN Rail

Housing Features

Housing Material	Polyamide
------------------	-----------

Dimensions

Product Depth	45.6 mm
Tool Size	3.5 mm[.138 in]
Wire Stripping Length	11 mm[.433 in]
Main Circuit Capacity - 2 Rigid Stranded Conductors per Screw Clamp	24 – 14 AWG
Main Circuit Capacity - Twin Ferrule per Screw Clamp	24 – 14 AWG
Main Circuit Capacity - 2 Flexible Conductors per Screw Clamp	24 – 14 AWG
Main Circuit Capacity - 1 Rigid Stranded Conductor per Screw Clamp	24 – 10 AWG
Main Circuit Capacity - 1 Non-Insulated Ferrule per Screw Clamp	.22 – 4 mm ²
Main Circuit Capacity - 1 Insulated Ferrule per Screw Clamp	.22 – 4 mm ²
Main Circuit Capacity - 1 Flexible Conductor per Screw Clamp	24 – 10 AWG
Product Length	45.6 mm[1.8 in]
Product Height	59.7 mm
Product Spacing	8 mm[.315 in]

Usage Conditions

Installation Temperature Range	-5 – 40 °C[23 – 104 °F]
Operating Temperature Range	-55 – 110 °C[-67 – 230 °F]

Industry Standards

IP Rating	IP20
UL Flammability Rating	UL 94V-0

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
------------------------------	-----------



EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	有害物质含量符合标准要求 No Restricted Substance(s) Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability


Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts




TE Part # 1SNK169999R0000
MC812PA




TE Part # 1SNA164800R0300
PR3.G2



TE Part # 1SNA167550R0200
FU525



TE Part # 1SNK160004R0000
MC812-YL




TE Part # 1SNA168700R2200
PR5




TE Part # 1SNA167548R0400
FU525



TE Part # 1SNK900624R0000
KCO



TE Part # 1SNA008290R1300
FU520



TE Part # 1SNK160000R0000
[MC812](#)




TE Part # 1SNK900613R0000
[PROCAP8](#)




TE Part # 1SNK900001R0000
[BAM4](#)



TE Part # 1SNA173523R1100
[PC81-10](#)



TE Part # 1SNA168500R1200
[PR4](#)



TE Part # 1SNA008291R0000
[FU520](#)




TE Part # 1SNK508960R0000
[ES4-SF](#)



TE Part # 1SNK900611R0000
[UMH](#)




TE Part # 1SNK900002R0000
[BAZ1](#)



TE Part # 1SNA168672R1100
[TGA8](#)




TE Part # 1SNK900604R0000
[CO](#)



TE Part # 1SNA173220R0500
[PR30](#)


Also in the Series | [ENTRELEC SNK](#)



[Modular Terminal Blocks\(319\)](#)




[Terminal Block & Strip Conducting Accessories\(67\)](#)



[Terminal Block & Strip Insulating Accessories\(31\)](#)


Customers Also Bought




TE Part #1SNK506410R0000
[ZS4-SF](#)



TE Part #CSH-SGFB-100-UFFR
[SMA to U.FL/MHF1 100mm 1.32 OD](#)




TE Part #374380-E
[STVTE 160 FI ABCDE VVVV 7-03 TL-S ** 2](#)



TE Part #163084-1
[RECEPTACLE](#)







TE Part #182661-1
CPC Cable Clamp Kit, Size 17, Large, UV



TE Part #183039-1
SIZE 17-14 CPC PLUG ASS'YSTD S




TE Part #292132-2
CT P/HDR BOX V 2P NAT



TE Part #1-966144-0
FER,WIRE,DBL,PL SLV,4.00/12,L12, GREY,LP



TE Part #1-1478420-0
N Str Plg PS 50Ohm Silver Pltd PSF1 /4M,



TE Part #F687753001
ACW0219-1.00-5(NS)

Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1SNK508415R0000_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1SNK508415R0000_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1SNK508415R0000_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

ENTRELEC Terminal Block - Master Catalog

ENTRELEC Terminal Block - Master Catalog

English

ZS4-SF1-R4

English

SNK SERIES TERMINAL BLOCKS

English

ENTRELEC Terminal Blocks Catalogue (RUS)

Agency Approvals

CE Declaration of Conformity

1SNK508415R0000

Screw Clamp Terminal Block, Fuse, Gray & Dark Gray, 8 mm [.315 in] Spacing, 2
Position, DIN Rail, -55 – 110 °C [-67 – 230 °F], ENTRELEC SNK



English