Apr.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD				
RATING	OPERATING TEMPERATURE RANGE	−25°C TO +85°C	STORAGE TEMPERATURE RANGE	−25°C TO +60°C
	OPERATING&STORAGE HUMIDTY RANGE	85 % MAX	APPLICABLE CABLE	CABLE DIAMETER : φ7.3±0.5

SPECIFICATIONS

ITEM	TEST METHOD	REQUIREMENTS	QT	AT
CONSTRUCTION				
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X

	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
⚠0					

REMARK

Unless otherwise specified, refer to JIS C 5402.

APPROVED	AO. SUZUKI	09. 10. 05
CHECKED	KN. ICHIKAWA	09. 10. 02
DESIGNED	TU. TANIGUCHI	09. 10. 02
DRAWN	TU. TANIGUCHI	09. 10. 02

Note QT:Qualification Test AT:Assurance Test X:Applicable Test

DRAWING NO. ELC4-126658-00

HRS	SPECIFICATION SHEET	PART NO.	DH-27-CMB(7.3)	
	HIROSE ELECTRIC CO., LTD.	CODE NO.	CL244-0032-8-00 ⚠0	1/

FORM HD0011-2-1