SERVICE ENTRANCE SUPPRESSOR(F), 160 KA, 120/208 V UN, 3PH Y 4W+G DIST SYSTEM

CATALOG NUMBER

SES160F208Y



The nVent ERICO SES160F Series is an enhanced version of the SES160B Series. The SES160F Surge-Filter is robust, with a 160 kA per phase surge rating. The high surge rating increases both survivability and life cycle. With the addition of a filter nuisance high frequency transients on the power distribution system are attenuated, protecting sensitive equipment. cUL® 1449 Listed SPD for Type 2 locations. Applications include service entrance, distribution, branch panels, MCC, lighting panels, HVAC, A/V systems, IT equipment, and more.

CERTIFICATIONS

FEATURES

- Compact design can be directly mounted to panel or installed in a small space
- Front-facing design eases installation and performance monitoring
- 160 kA 8/20 µs maximum surge rating per phase
- Up to 57 dB attenuation (10 kHz to 100 MHz)
- Optional Flush Mounting Plate
- Ground reference monitoring triggers an alarm when N-PE mode exceeds 20 volts
- 10-year limited warranty

PRODUCT ATTRIBUTES

- Nominal System Voltage (Un): 120/208 V
- Distribution System: 3Ph Y 4W+G
- Max Continuous Operating Voltage (Uc): 150/300 V
- Filtering: -40 dB @ 100 kHz
- Frequency: 0 - 600 Hz
- Short Circuit Current Rating (SCCR): 200 kA
- Nominal Discharge Current (In), Per Mode: 20 kA 8/20 µs
- Max Discharge Current (Imax), Per Phase: 160 kA 8/20 µs

Voltage Protection Rating (VPR), L-L: 1200 V

Voltage Protection Rating (VPR), L-N: 700 V

Voltage Protection Rating (VPR), L-PE: 700 V

Voltage Protection Rating (VPR), N-PE: 600 V

Protection Modes: All modes protected

Status Indication: 1 green LED per line;Audible alarm;Change-over contact (Form C dry), 240 VAC/2A

Remote Contact Switching Capacity: 2 A @ 240 V

Remote Contacts: Yes

Lead Length: 18

Temperature: -40 to 185 °F

Enclosure Material: Polycarbonate

Enclosure Rating: NEMA®-4X;UL® 50E Type 4

Mounting: 3/4” straight nipple

Unit Weight: 1.38 lb

Certification Details: CSA C22.2 No. 269.2;UL® 1283 Edition 7;UL® 1449 Edition 5 Type 2, 20 kA Mode


Complies With: ANSI®/IEEE® C62.41.2-2002 Cat A, Cat B, Cat C;ANSI®/IEEE® C62.41.1-2002 Cat A, Cat B, Cat C;ANSI®/IEEE® C62.45-2002 Cat A, Cat B, Cat C

Depth (D): 3.06"

Height (H): 2 3/4"

Width (W): 7.95"

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America
+1.800.753.9221
Option 1 – Customer Care
Option 2 – Technical Support

Europe
Netherlands:
+31 800-0200135
France:
+33 800 901 793

Europe
Germany:
800 1890272
Other Countries:
+31 13 5835404

APAC
Shanghai:
+ 86 21 2412 1618/19
Sydney:
+61 2 9751 8500

nVent

Our powerful portfolio of brands:

nVent.com **CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER**

© 2024 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.

nVent reserves the right to change specifications without notice.