




Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: .32 – .82 mm²

Mating Tab Width: 4.75 mm [.187 in]

Mating Tab Thickness: .81 mm [.032 in]

Features

Product Type Features

|                 |     |
|-----------------|-----|
| Insertion Force | Low |
|-----------------|-----|

Configuration Features

|                                   |               |
|-----------------------------------|---------------|
| Compatible With Wire & Cable Type | Discrete Wire |
| Connection Capacity               | Single        |

Electrical Characteristics

|                |       |
|----------------|-------|
| Voltage Rating | 600 V |
|----------------|-------|

Body Features

|                     |       |
|---------------------|-------|
| Insulation Material | Nylon |
|---------------------|-------|

Contact Features

|                                |                  |
|--------------------------------|------------------|
| Quick Disconnect Terminal Type | Receptacle       |
| Mating Tab Width               | 4.75 mm[.187 in] |
| Mating Tab Thickness           | .81 mm[.032 in]  |
| Terminal Orientation           | Flag             |
| Contact Base Material          | Brass            |



|                           |         |
|---------------------------|---------|
| Terminal Plating Material | Tin     |
| Crimp Type                | F-Crimp |
| Barrel Type               | Closed  |

Termination Features

|                       |              |
|-----------------------|--------------|
| Product Terminates To | Wire & Cable |
|-----------------------|--------------|

Mechanical Attachment

|                         |        |
|-------------------------|--------|
| Wire Insulation Support | With   |
| Mating Retention Type   | Dimple |

Dimensions

|                                      |                   |
|--------------------------------------|-------------------|
| Product Length                       | 13.08 mm[.515 in] |
| Compatible Insulation Diameter Range | 4.19 mm[.165 in]  |
| Terminal Material Thickness          | .41 mm[.016 in]   |
| Wire Size                            | .32 – .82 mm²     |

Usage Conditions

|                             |                            |
|-----------------------------|----------------------------|
| Insulation Option           | Fully Insulated            |
| Operating Temperature Range | -40 – 110 °C[-40 – 230 °F] |

Industry Standards

|                                           |          |
|-------------------------------------------|----------|
| Compatible With Agency/Standards Products | UL       |
| UL Flammability Rating                    | UL 94V-2 |

Packaging Features

|                    |            |
|--------------------|------------|
| Packaging Quantity | 2200       |
| Packaging Method   | Strip/Reel |

Other

|              |       |
|--------------|-------|
| Barrel Color | Black |
|--------------|-------|

Product Compliance

For compliance documentation, visit the product page on [TE.com](#)>

|                                               |                                              |
|-----------------------------------------------|----------------------------------------------|
| EU RoHS Directive 2011/65/EU                  | Compliant                                    |
| EU ELV Directive 2000/53/EC                   | Compliant                                    |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold      |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JUNE 2025 (250) |



Candidate List Declared Against: JUNE 2025 (250)  
Does not contain REACH SVHC

|                           |                                                                                  |
|---------------------------|----------------------------------------------------------------------------------|
| Halogen Content           | Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free |
| Solder Process Capability | Not applicable for solder process capability                                     |

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # 90390-3  
DIES ULTRA-FAST FASTON 22-18 DIE SET



TE Part # 7-2150278-7  
OCEAN\_2.0\_SPARE\_PART\_KIT-201D



TE Part # 2150278-2  
OCEAN\_2.0\_APPLICATOR-E-201D-SEA

Also in the Series | Ultra-Fast 187

A photograph showing several Ultra-Fast 187 Quick Disconnects, which are small, rectangular, gold-colored components with a central slot and a small tab on one side.

[Quick Disconnects\(46\)](#)

Customers Also Bought




TE Part #33469  
TERMINAL, SOLIS R 4 1/4



TE Part #34294  
TAB, PIDG 22-16



TE Part #52197  
TERMINAL, SOLIS R 6 10




TE Part #165085-1  
PG WIRE PIN YELLOW




TE Part #322455  
TERMINAL, SOLIS R 12-10 10




TE Part #326861  
PIDG SPD 22-16 COMM 22-18MIL 6



TE Part #2-520336-2  
ULTRA-FAST 187 ASY REC 22-18 TPBR



TE Part #3-521247-2  
ULTRA-FAST 187 ASY REC 16-14 AWG TPBR



TE Part #8-1377174-7  
SMP 9-0160483-1



TE Part #1625999-9  
HSC100 18R 5%

Documents

Product Drawings

ULTRA-FAST 187 ASY REC 22-18 AWG TPBR

English

CAD Files

3D PDF

3D

Customer View Model

ENG\_CVM\_CVM\_9-520336-2\_M.2d\_dxf.zip

English

Customer View Model

ENG\_CVM\_CVM\_9-520336-2\_M.3d\_igs.zip

English

Customer View Model

ENG\_CVM\_CVM\_9-520336-2\_M.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages



Ultra-Fast and Ultra Fast Plus

English

Product Specifications

Application Specification

English