Specification Sheet

Part Number: 157-00329



Offset mount allows wire or cable to be attached beside mounting hole instead of directly above it.
Reusable fastener can be extracted from threaded or nonthreaded holes using a 5/16" hex driver.

Delivers high extraction force for reliable performance, yet it’s easy to install.

Heat stabilized material provides excellent resistance to high temperatures.

Blind Hole Mount Cable Tie, Offset, 8"L, 0.25" Thread/Non-Thread Hole, 50lb, PA66HS, Black, 500/bg

Article Number	157-00329
Type	T50ROSBHMBSO18
Color	Black (BK)
Quantity Per	bag
Product Description	Blind Hole Mount Offset Cable Ties secure bundles beside the mounting hole instead of directly above it. The unique design includes a heat stabilized cable tie and formula-matched, hex-head fastener that features a low insertion force and aggressively resists pull off. Performs equally well in threaded or non-threaded blind holes. Since cable or wire bundle is beside the fastener, the assembly can be removed using a hex driver from the mounting hole without cutting the cable tie. The fastener can then be reused.

Short Description	Blind Hole Mount Cable Tie, Offset, 8"L, 0.25" Thread/Non-Thread Hole, 50lb, PA66HS, Black, 500/bg
Global Part Name	T50ROSBHMBSO18-PA66HS-BK

Minimum Tensile Strength (Imperial)	50.0
Minimum Tensile Strength (Metric)	225
Length L (Imperial)	8.0
Length L (Metric)	203.2
Offset Length (Imperial)	0.71
Offset Length (Metric)	18.0
Fixation Method	Blind Plug
Identification Plate Position	none
Releasable Closure	No
Width W (Imperial)	0.185
Width W (Metric)	4.7
Bundle Diameter Min (Imperial)	0.08
Bundle Diameter Min (Metric)	2.0
Bundle Diameter Max (Imperial)	1.97

Bundle Diameter Max (Metric)	50.0
Height H (Imperial)	0.736
Height H (Metric)	18.7
Diameter D (Imperial)	0.25
Diameter D (Metric)	6.35
Mounting Hole Diameter D (Imperial)	0.246 - 0.253
Mounting Hole Diameter D (Metric)	6.25 - 6.45 mm
Mounting Hole Diameter D Min (Imperial)	0.25
Mounting Hole Diameter D Max (Imperial)	0.25
Mounting Hole Diameter D Max (Metric)	6.45

Material	Polyamide 6.6 heat stabilized (PA66HS)
Material Shortcut	PA66HS
Flammability	UL 94 V-2
UV Resistant (Yes/No)	No
Operating Temperature	-40°F to +257°F (-40°C to +125°C)

Reach Compliant (Article 33)	No
ROHS Compliant	Yes
Package Quantity (Imperial)	500
Package Quantity (Metric)	500
Customs Number	3926909988

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2024 HellermannTyton. All Rights Reserved.