NTB6412AN, NTP6412AN, NVB6412AN

N-Channel Power MOSFET 100 V, 58 A, 18.2 mΩ

Features

- Low $R_{DS(on)}$
- High Current Capability
- 100% Avalanche Tested
- NVB Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC−Q101 Qualified and PPAP Capable
- These Devices are Pb−Free and are RoHS Compliant

MAXIMUM RATINGS (T_J = 25°C Unless otherwise specified)

Parameter			Symbol	Value	Unit
Drain−to−Source Voltage			V_{DSS}	100	V
Gate−to−Source Voltage − Continuous			V_{GS}	±20	V
Continuous Drain Current $R_{\theta JC}$	Steady State	T_C = 25°C	I_D	58	A
		T_C = 100°C		41	
Power Dissipation $R_{\theta JC}$	Steady State	T_C = 25°C	P_D	167	W
Pulsed Drain Current	t_p = 10 μs		I_{DM}	240	A
Operating Junction and Storage Temperature Range			T_J, T_{stg}	−55 to +175	°C
Source Current (Body Diode)			I_S	58	A
Single Pulse Drain−to−Source Avalanche Energy (V_{DD} = 50 Vdc, V_{GS} = 10 Vdc, $I_{L(pk)}$ = 44.7 A, L = 0.3 mH, R_G = 25 Ω)			E_{AS}	300	mJ
Lead Temperature for Soldering Purposes, 1/8″ from Case for 10 Seconds			T_L	260	°C

THERMAL RESISTANCE RATINGS

Parameter	Symbol	Max	Unit
Junction−to−Case (Drain) Steady State	$R_{\theta JC}$	0.9	°C/W
Junction−to−Ambient (Note 1)	$R_{\theta JA}$	33	

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.


1. Surface mounted on FR4 board using 1 sq in pad size, (Cu Area 1.127 sq in [2 oz] including traces).


ON Semiconductor®

www.onsemi.com


$V_{(BR)DSS}$	$R_{DS(ON)}$ MAX	I_D MAX (Note 1)
100 V	18.2 mΩ @ 10 V	58 A

N−Channel







TO−220AB
CASE 221A
STYLE 5



D^2PAK
CASE 418B
STYLE 2

MARKING DIAGRAM & PIN ASSIGNMENT





6412AN = Specific Device Code
G = Pb−Free Device
A = Assembly Location
Y = Year
WW = Work Week

ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 5 of this data sheet.

© Semiconductor Components Industries, LLC, 2015

ELECTRICAL CHARACTERISTICS (T_J = 25°C Unless otherwise specified)

Characteristics	Symbol	Test Condition		Min	Typ	Max	Unit
OFF CHARACTERISTICS							
Drain−to−Source Breakdown Voltage	$V_{(BR)DSS}$	V_{GS} = 0 V, I_D = 250 μA		100			V
Drain−to−Source Breakdown Voltage Temperature Coefficient	$V_{(BR)DSS}/T_J$				103		mV/°C
Zero Gate Voltage Drain Current	I_{DSS}	V_{GS} = 0 V, V_{DS} = 100 V	T_J = 25°C			1.0	μA
			T_J = 125°C			100	
Gate−to−Source Leakage Current	I_{GSS}	V_{DS} = 0 V, V_{GS} = ±20 V				±100	nA
ON CHARACTERISTICS (Note 2)							
Gate Threshold Voltage	$V_{GS(th)}$	V_{GS} = V_{DS}, I_D = 250 μA		2.0		4.0	V
Negative Threshold Temperature Coefficient	$V_{GS(th)}/T_J$				9.2		mV/°C
Drain−to−Source On−Resistance	$R_{DS(on)}$	V_{GS} = 10 V, I_D = 58 A			16.8	18.2	mΩ
		V_{GS} = 10 V, I_D = 20 A			15.6	18.2	
Forward Transconductance	g_{FS}	V_{DS} = 5 V, I_D = 20 A			31		S
CHARGES, CAPACITANCES & GATE RESISTANCE							
Input Capacitance	C_{iss}	V_{DS} = 25 V, V_{GS} = 0 V, f = 1 MHz			2700	3500	pF
Output Capacitance	C_{oss}				400	500	
Reverse Transfer Capacitance	C_{rss}				150		
Total Gate Charge	$Q_{G(TOT)}$	V_{GS} = 10 V, V_{DS} = 80 V, I_D = 58 A			73	100	nC
Threshold Gate Charge	$Q_{G(TH)}$				2.5		
Gate−to−Source Charge	Q_{GS}				13.5		
Gate−to−Drain Charge	Q_{GD}				35		
Plateau Voltage	V_{GP}				5.6		V
Gate Resistance	R_G				2.2		Ω
SWITCHING CHARACTERISTICS, V_{GS} = 10 V (Note 3)							
Turn−On Delay Time	$t_{d(on)}$	V_{GS} = 10 V, V_{DD} = 80 V, I_D = 58 A, R_G = 6.2 Ω			16		ns
Rise Time	t_r				140		
Turn−Off Delay Time	$t_{d(off)}$				70		
Fall Time	t_f				126		
DRAIN−SOURCE DIODE CHARACTERISTICS							
Forward Diode Voltage	V_{SD}	I_S = 58 A	T_J = 25°C		0.96	1.3	V
			T_J = 125°C		0.89		
Reverse Recovery Time	t_{rr}	V_{GS} = 0 V, I_S = 58 A, dI_{SD}/dt = 100 A/μs			85		ns
Charge Time	t_a				60		
Discharge Time	t_b				25		
Reverse Recovery Charge	Q_{RR}				270		nC

2. Pulse Test: Pulse Width ≤ 300 μs, Duty Cycle ≤ 2%.
3. Switching characteristics are independent of operating junction temperatures.




Figure 1. On−Region Characteristics




Figure 2. Transfer Characteristics




Figure 3. On−Region versus Gate Voltage




Figure 4. On−Resistance versus Drain Current and Gate Voltage




Figure 5. On−Resistance Variation with Temperature




Figure 6. Drain−to−Source Leakage Current versus Voltage




Figure 7. Capacitance Variation




Figure 8. Gate−to−Source Voltage and Drain−to−Source Voltage versus Total Charge




Figure 9. Resistive Switching Time Variation versus Gate Resistance




Figure 10. Diode Forward Voltage versus Current




Figure 11. Maximum Rated Forward Biased Safe Operating Area




Figure 12. Maximum Avalanche Energy versus Starting Junction Temperature





Figure 13. Thermal Response

ORDERING INFORMATION

Device	Package	Shipping†
NTB6412ANG	D^{2}PAK (Pb−Free)	50 Units / Rail
NTB6412ANT4G	D^{2}PAK (Pb−Free)	800 / Tape & Reel
NTP6412ANG	TO−220 (Pb−Free)	50 Units / Rail
NVB6412ANT4G	D^{2}PAK (Pb−Free)	800 / Tape & Reel


†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.



D²PAK 3
CASE 418B–04
ISSUE L


DATE 17 FEB 2015

SCALE 1:1



NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. 418B–01 THRU 418B–03 OBSOLETE, NEW STANDARD 418B–04.

	INCHES		MILLIMETERS	
DIM	MIN	MAX	MIN	MAX
A	0.340	0.380	8.64	9.65
B	0.380	0.405	9.65	10.29
C	0.160	0.190	4.06	4.83
D	0.020	0.035	0.51	0.89
E	0.045	0.055	1.14	1.40
F	0.310	0.350	7.87	8.89
G	0.100 BSC		2.54 BSC	
H	0.080	0.110	2.03	2.79
J	0.018	0.025	0.46	0.64
K	0.090	0.110	2.29	2.79
L	0.052	0.072	1.32	1.83
M	0.280	0.320	7.11	8.13
N	0.197 REF		5.00 REF	
P	0.079 REF		2.00 REF	
R	0.039 REF		0.99 REF	
S	0.575	0.625	14.60	15.88
V	0.045	0.055	1.14	1.40



VIEW W–W 1 | VIEW W–W 2 | VIEW W–W 3

STYLE 1:
PIN 1. BASE
2. COLLECTOR
3. EMITTER
4. COLLECTOR

STYLE 2:
PIN 1. GATE
2. DRAIN
3. SOURCE
4. DRAIN

STYLE 3:
PIN 1. ANODE
2. CATHODE
3. ANODE
4. CATHODE

STYLE 4:
PIN 1. GATE
2. COLLECTOR
3. EMITTER
4. COLLECTOR

STYLE 5:
PIN 1. CATHODE
2. ANODE
3. CATHODE
4. ANODE

STYLE 6:
PIN 1. NO CONNECT
2. CATHODE
3. ANODE
4. CATHODE

MARKING INFORMATION AND FOOTPRINT ON PAGE 2


ON Semiconductor and ON are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. ON Semiconductor does not convey any license under its patent rights nor the rights of others.

© Semiconductor Components Industries, LLC, 2019

D²PAK 3
CASE 418B−04
ISSUE L

DATE 17 FEB 2015

GENERIC
MARKING DIAGRAM*




IC **Standard** **Rectifier**

xx	= Specific Device Code
A	= Assembly Location
WL	= Wafer Lot
Y	= Year
WW	= Work Week
G	= Pb−Free Package
AKA	= Polarity Indicator

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, “G” or microdot “ ▪”, may or may not be present.

SOLDERING FOOTPRINT*



DIMENSIONS: MILLIMETERS

*For additional information on our Pb−Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

DOCUMENT NUMBER:	**98ASB42761B**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped “CONTROLLED COPY” in red.	
DESCRIPTION:	**D²PAK 3**		**PAGE 2 OF 2**

ON Semiconductor and ON are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. ON Semiconductor does not convey any license under its patent rights nor the rights of others.

© Semiconductor Components Industries, LLC, 2019

onsemi, , and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at www.onsemi.com/support/sales