353716-2 ✔ ACTIVE


Dynamic Series | Dynamic 3000 Series


TE Internal #: 353716-2

Gold (Au), Tab Contact, 16 – 14 AWG, 250 VAC, 1.23 – 2.27 mm² Wire, Discrete Wire, Crimp, Copper Alloy, Power & Signal, Dynamic 3000 Series

View on TE.com >

Connectors > Contacts > Connector Contacts > Contact: Component To Wire; 15A, 28-14 wire size

Contact Type: **Tab**

Contact Mating Area Plating Material: **Gold (Au)**

Operating Voltage: **250 VAC**

Compatible With Wire & Cable Type: **Discrete Wire**

Wire Size: **16 – 14 AWG**

All Contact: Component To Wire; 15A, 28-14 wire size (91)

Features

Product Type Features

Discrete Wire Type	Solid or Stranded
Sealable	No

Configuration Features

Compatible With Wire & Cable Type	Discrete Wire

Electrical Characteristics

Operating Voltage	250 VAC

Contact Features

Barrel Type	Open
Contact Length	25.8 mm[1.016 in]
Contact Type	Tab
Contact Mating Area Plating Material	Gold (Au)
Contact Base Material	Copper Alloy

Contact Current Rating (Max)	15 A
Mating Tab Width	2 mm[.08 in]
Mating Tab Thickness	.64 mm[.025 in]
Contact Mating Area Plating Material Thickness	.38 µm[15 µin]
Contact Orientation	Straight

Termination Features

Termination Method to Wire & Cable	Crimp
Product Terminates To	Wire & Cable

Mechanical Attachment

Wire Insulation Support	With

Dimensions

Wire Size	1.23 – 2.27 mm²
Compatible Insulation Diameter Range	3.1 – 3.4 mm[.122 – .133 in]

Usage Conditions

Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]

Operation/Application

Circuit Application	Power & Signal

Packaging Features

Packaging Quantity	12000
Packaging Method	Reel & Box

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free

Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach


Compatible Parts



TE Part # CAT-D9934-A75B
Receptacle and Tab Housing: 5.08 mm Pitch, 250-600V




TE Part # 2151073-1
OCEAN_2.0_APPLICATOR-S-100F110O-RSM



TE Part # 2151073-2
OCEAN_2.0_APPLICATOR-S-100F110OA-RSA



TE Part # 91561-1
CCII D-3 3L REC TAB 16-14 ASSY



TE Part # CAT-D9934-A75A
Receptacle and Tab Housing: 3.81 mm pitch, 250V




TE Part # 2305570-1
Strip Terminal Cutter-Side Feed-No Crimp



TE Part # CAT-D9934-A75C
Receptacle and Tab Housing: 5.08 mm pitch, 600V



TE Part # 2255149-1
MINI SAHT D3000-3L



TE Part # 7-2151073-7
OCEAN_2.0_SPARE_PART_KIT-100F110O




TE Part # 234168-1
EXTRACTION TOOL(DYNAMIC D-3)

Also in the Series | Dynamic 3000 Series



Connector Contacts(94)



Connector Hardware(8)




Power Contacts(94)



Rectangular Connector Housings(143)



Rectangular Power Connectors(443)



Standard Rectangular Connectors(167)



Wire-to-Board Connector Assemblies & Housings(92)

Customers Also Bought



TE Part #1-177662-2

D3100 HDR,5POS SINGLE ROW SMT H PdNi



TE Part #1-178128-4

DYNAMIC 3200 REC HSG 4P SGL



TE Part #1827691-3

DYNATAP 3200 TAP ASSY 24P BOTTOM PdNI



TE Part #2382569-1

32POS,NANOMQS,REC HSG,UNSLD, COD A,STD

TE Part #224155-1

EXTR TL, HIGH CURRENT TYPE XII

TE Part #2428586-2

2POS,CSJ1800,HDR ASSY,COD B

TE Part #2434942-1

MCON 1.2,TERMINAL,LL TAB SWS SN

TE Part #2435084-1

MT 2,TERMINAL,REC 1.6 CONTACT SWS SN

TE Part #2441458-1

22POS,HYBRID,TAB HSG ASSY,SLD, COD A

TE Part #1-2477644-1

32POS,HYBRID,TAB HSG ASSY,SLD, COD A

Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_353716-2_C.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_353716-2_C.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_353716-2_C.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Application Specification

English

Instruction Sheets

Instruction Sheet (non U.S.)

English

MULTIPLE ENCLOSURE 67M D1200 15POS. TAB PLUG

Japanese

Instruction Sheet (non U.S.)

Japanese

Agency Approvals

TUV Certificate

English