
2013289-2 ✔ ACTIVE


TE Internal #: 2013289-2

SO DIMM Sockets, Double Data Rate (DDR) 3, Stack Height .205 in [5.2 mm], Right Angle Module Orientation, 204 Position, .024 in [.6 mm] Centerline

View on TE.com >

Connectors > Socket Connectors > Memory Sockets > SO DIMM Sockets







DRAM Type: **Double Data Rate (DDR) 3**

Stack Height: **5.2 mm [.205 in]**

Module Orientation: **Right Angle**

Number of Positions: **204**

Centerline (Pitch): **.6 mm [.024 in]**

Features

Product Type Features

Connector System	Cable-to-Board
Connector & Contact Terminates To	Printed Circuit Board
DRAM Type	Double Data Rate (DDR) 3

Configuration Features

Number of Bays	2
Number of Keys	1
Number of Rows	2
Module Orientation	Right Angle
Number of Positions	204

Electrical Characteristics

DRAM Voltage	1.5 V

Signal Characteristics

SGRAM Voltage	1.5 V

Body Features

Ejector Location	Both Ends
Latch Material	Stainless Steel
Latch Plating Material	Tin
Module Key Type	SGRAM
Ejector Type	Locking
Connector Profile	Standard

Contact Features

Memory Socket Type	Memory Card
PCB Contact Termination Area Plating Material	Gold
Contact Base Material	Copper Alloy
Contact Current Rating (Max)	.5 A
Contact Mating Area Plating Material	Gold
Contact Mating Area Plating Material Thickness	.254 µm[10 µin]

Termination Features

Insertion Style	Cam-In
Termination Method to Printed Circuit Board	Surface Mount

Mechanical Attachment

Mating Alignment Type	Standard Keying
PCB Mount Retention	With
PCB Mount Retention Type	Solder Peg
Connector Mounting Type	Board Mount

Housing Features

Housing Material	High Temperature Thermoplastic
Housing Color	Black
Centerline (Pitch)	.6 mm[.024 in]

Dimensions

Stack Height	5.2 mm[.205 in]
Row-to-Row Spacing	8.2 mm[.322 in]

Usage Conditions

Operating Temperature Range	-55 - 85 °C[-67 - 185 °F]

Operation/Application

Circuit Application	Power

Industry Standards

UL Flammability Rating	UL 94V-0

Packaging Features

Packaging Quantity	20
Packaging Method	Semi-Hard Tray Assembly

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Reflow solder capable to 260°C

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



TE Part # 2309407-1
DDR4 SODIMM 260P 4.0H STD

Customers Also Bought



TE Part # 823748-000
382A012-4-0



TE Part # 1-2129458-1
DC Power Jack Conn DIP type 10.7A



TE Part # 4-2176091-4
RP 2A 0.25W 162R 0.1% 25PPM 1K RL



TE Part # 7-2176092-9
RP 2A 0.25W 5K11 0.1% 25PPM 1K RL




TE Part # 2213766-1
AV19 SPM 3A POWER LED WHITE 12V




TE Part # 1-2213766-5
AV19 SPM 3A POWER LED GREEN 24V



TE Part # 3-2176093-9
RP 2A 0.25W 23K7 0.1% 25PPM 1K RL



TE Part # 2-2176306-6
RP 1E 0.1W 2K1 0.1% 25PPM 5K RL



TE Part # 5-2176305-5
RP 1E 0.1W 392R 0.1% 25PPM 5K RL



TE Part # CSJ-RGFB-100-MHF4
RP-SMA to MHF4 100mm 0.81 OD

Documents

Product Drawings

SEMI-HARD TRAY DDR3 204P 5.2H STD Au0.25

English

CAD Files

Customer View Model

ENG_CVM_CVM_2013289-2_B.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2013289-2_B.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2013289-2_B.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditionsof use.

Datasheets & Catalog Pages

DDR3 DIMM Sockets Flyer 6-1773454-7 05/09

English

6-1773457-3_DDR3_DIMM_SOCKETS

Product Specifications

Product Specification

English