


1		2		3		4		5		6		7		8	
				REV.		ECN NO.		DATE		SIGN		DESCRIPTION			
				B		LEN-9A0230~233		2009/04/14		Li Xiu Zhi		Change SR View & Update Note			
				C		LEN1480040~044		2014/07/28		Vicky		Update Logo			
F															
E															
D															
C															
B															
A															
UNIT:mm															
TOLERANCE															
±0.5 mm															
TITLE															
Middle Cable Lock 5Pin F Conn M Pin															
SCALE															
1:1															
SIZE															
A4															
SHEET															
1 OF 1															
REV.															
C															
WC-REV.															
A.1															
QC: Inspection item															
Amphenol LTW															
安費諾亮泰企業股份有限公司															
ITEM NO															
CB-05AFMM-LL7AXX															
DWG NO															
CB-05AFMM-LL7AXX															
CUSTOMER															
ALTW															
DRAWN BY															
Vicky															
CHECKED BY															
Sam															
APPROVED BY															
Rita															
DATE															
2014-07-28															
DATE															
2014-07-28															
DATE															
2014-07-28															
FMM10702-01-02A1															

REV.	ECN NO.	DATE	SIGN	DESCRIPTION
B	LEN-9A0230~233	2009/04/14	Li Xiu Zhi	Change SR View & Update Note
C	LEN1480040~044	2014/07/28	Vicky	Update Logo


ALTW

ALTW

ALTW





Conn.



1 CB-05AFMM-LL7000
Color: Black

2 Cable



Pin Assignments
Front View

5	Green	綠
4	White	白
3	Black	黑
2	Blue	藍
1	Brown	棕
Conn.	Wire Color	
	Pin Out	

CB-05AFMM-LL7AXX

XX :01~99Meters
01 :01Meter
02 :02Meters
:
99 :99Meters

Cable Length(L):01~99Meters

Note:

- * Important Dimension To Check
- * Waterproof Rate: IP67
- * Housing: Nylon+GF, Black
- * Male Pin: Copper Alloy, Gold Plated
- * Lock Nut: Nylon+GF, Black
- * O-Ring: EPDM, Black
- * Cable: UL2464 20AWG*5C+Drain+Al/My, Black,PVC Jacket,UV Resistant,OD=6.0
- * Cable Length Tolerance: 01M:±40mm
02M~05M:±60mm
06M~10M:±100mm
11M~30M:±200mm
31M~99M:±500mm