

ATGBICS S-54LC80D MikroTik compatible Transceiver SFP
1000Base-BX-D (Tx1550nm/Rx1490nm SMF 80km LC DOM Ind Temp)



Brand : ATGBICS

Product code: S-54LC80D-C

Product name : S-54LC80D MikroTik compatible Transceiver
SFP 1000Base-BX-D (Tx1550nm/Rx1490nm SMF 80km LC
DOM Ind Temp)

S-54LC80D MikroTik compatible Transceiver SFP 1000Base-BX-D (Tx1550nm/Rx1490nm SMF 80km LC
DOM Ind Temp)

ATGBICS S-54LC80D MikroTik compatible Transceiver SFP 1000Base-BX-D (Tx1550nm/Rx1490nm SMF
80km LC DOM Ind Temp):

ATGBICS MikroTik® compatible S-54LC80D SFP 1000Base-BX form factor network transceiver supports a distance of up to 80km over single-mode fibre (SMF) using a wavelength of 1550/1490nm via an LC Simplex connector. This product operates within an industrial temperature range. Digital optical monitoring (DOM) support is also present enabling real-time monitoring of the parameters of the fibre optic transceiver. Our product meets the specification of MikroTik® S-54LC80D and we proudly offer a compatibility guarantee and limited lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA (Multi-Source Agreement) and IEEE standards & protocols.

Performance		Features	
SFP transceiver type *	Fiber optic	Hot-Plug support	✔
Maximum data transfer rate *	1000 Mbit/s	Hot-swap	✔
Interface type *	SFP	Easy to install	✔
Single-mode fiber (SMF) supported	✔	Brand compatibility	MikroTik
Multi-mode fiber (MMF) supported	✘	Certificates	
Fiber optic connector	LC	Compliance certificates	TÜV mark, UKCA, Electromagnetic Compatibility (EMC), REACH, Federal Communications Commission (FCC), RoHS, CE
SFP transceiver standard	BX-D		
Maximum transfer distance	80000 m	Certification	CE, EMC, FCC, REACH, RoHS, TÜV
Wavelength	1550 nm		
Ethernet LAN	✔	Sustainability	
Ethernet interface type	Gigabit Ethernet	Doesn't contain	Lead
Fiber ethernet cabling technology	1000BASE	Operational conditions	
Export Control Classification Number (ECCN)	5A991	Minimum operating temperature	-40 °C
Features		Maximum operating temperature	85 °C
Product colour	Silver	Operating temperature (T-T)	-40 - 85 °C
Housing material	Metal	Storage temperature (T-T)	-40 - 85 °C
Plug and Play	✔	Operating relative humidity (H-H)	0 - 95%
		Storage relative humidity (H-H)	0 - 95%
		Logistics data	
		Country of origin	United Kingdom

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.