





THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.

REV.	ECN NO.	DATE	SIGN	DESCRIPTION
B	LEN-9A0128~131	2009/04/17	Li Xiu Zhi	Change SR View & Update Note
C	LEN1480581~584	2014/08/22	Vicky	Update Logo



Conn.



Pin Assignments
Front View

10	Orange	橘
9	Black	黑
8	Red	紅
7	Pink	粉紅
6	Gray	灰
5	Yellow	黃
4	Green	綠
3	White	白
2	Blue	藍
1	Brown	棕
Conn.	Wire Color	
	Pin Out	

CD-10AFFM-SL7AXX
XX : 01~99Meters
01 : 01Meter
02 : 02Meters
:
99 : 99Meters
Cable Length(L): 01~99Meters

- Note:**
- * $\varnothing$ Important Dimension To Check
 - * Waterproof Rate: IP67
 - * Housing: Nylon+GF, Black
 - * Female Pin: Copper Alloy, Gold Plated
 - * Screw Nut: Nylon+GF, Black
 - * O-Ring: EPDM, Black
 - * Cable: UL2464 24AWG*10C+Drain+Al/My, Black,PVC Jacket,UV Resistant,OD=6.5
 - * Cable Length Tolerance: 01M:±40mm
02M~05M:±60mm
06M~10M:±100mm
11M~30M:±200mm
31M~99M:±500mm

UNIT:mm		TITLE
TOLERANCE	±0.5 mm	Middle Cable Screw 10Pin F Conn F Pin
SCALE	1:1	SIZE A4
REV.	C	SHEET 1 OF 1
	WC-REV. A.1	$\varnothing$ Inspection item

Amphenol LTW
安費諾亮泰企業股份有限公司

ITEM NO	DWG NO	CUSTOMER	DRAWN BY	CHECKED BY	APPROVED BY	DATE
	CD-10AFFM-SL7AXX	ALTW	Vicky	Sam	Rita	2014-08-22
						2014-08-22
						2014-08-22